

# ISO/TR 21186-2:2021 (E)

## Cooperative intelligent transport systems (C-ITS) — Guidelines on the usage of standards — Part 2: Hybrid communications

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
5	Motivations for hybrid communications support
5.1	Connected and cooperative mobility
5.2	Examples of use cases requiring a diversity of access technologies
5.2.1	Road hazard notification (use case 1)
5.2.2	Emergency call (use case 2)
5.2.3	Public transport (use case 3)
5.3	Hybrid communication technologies
5.4	Unified communication and data management architecture
5.4.1	Requirements for the unified communication and data management architecture
5.4.2	Supporting a diversity of applications with diverging communication needs
5.4.3	Supporting a diversity of communication paths
5.4.4	Supporting a diversity of access technologies and protocols
5.4.4.1	Networked communications in the ITS station
5.4.4.2	Localized communications in the ITS station
6	The ITS station architecture and functionalities in support of hybrid communications
6.1	Origins of the ITS station architecture
6.2	Detailed ITS station architecture
6.3	Design principles of the ITS station architecture
6.4	ITS station functionalities in support for hybrid communications
6.5	ITS station management entity
6.6	ITS station capabilities
6.7	ITS station service managed entity (ITS-S MSE)
6.8	Management of data flow types (ITS-S flow type)
6.9	Management of communication paths (ITS-S path)
6.10	Management of communication profiles (ITS-SCP)
6.11	Management of communication handovers
6.12	Management of globally unique identifiers
6.13	Standards necessary in support of hybrid communications
7	How to develop ITS application standards
7.1	Generic development principle
7.2	Specifying ITS-S application process
7.3	Defining data flow communication requirements
7.4	Registering communication requirements
7.5	Transmitting data