ISO 20730-1:2021 (E)

Road vehicles — Vehicle interface for electronic Periodic Technical Inspection (ePTI) — Part 1: Application and communication requirements

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Symbols and abbreviated terms

5 How to read this document

- 5.1 Layout of the document
- 5.2 Use case structure explanation
- 5.3 Requirements statement structure
- 5.4 ePTI application example

6 ePTI inspection modules and use cases overview and principles

- 6.1 Basic principles
- 6.2 ePTI inspection modules

7 IM-1 – Discover ePTI data link and ePTI-relevant system(s)

- 7.1 UC 1.1 – Discover ePTI data link
- 7.2 UC 1.2 – Discover ePTI-relevant system(s)

8 IM-2 – Authentication, authorisation

- 8.1 UC 2.1 – ePTI external test equipment authentication
- 8.2 UC 2.2 – Vehicle ECU authentication

9 IM-3 – Query available ePTI identifier(s)

- 9.1 UC 3.1 – Query supported data identifier(s)
- 9.2 UC 3.2 – Query supported routine identifier(s)
- 9.3 UC 3.3 – Query supported input/output control identifier(s)

10 IM-4 – Query ePTI system information

- 10.1 UC 4.1 – Query vehicle identification number
- 10.2 UC 4.2 – Query vehicle odometer value
- 10.3 UC 4.3 – Query system's software number
- 10.4 UC 4.4 – Identify installed system's software integrity information
- 10.5 UC 4.5 – Query information from system

11 IM-5 – Query system's self-test completion and error information

- 11.1 UC 5.1 – Query system's self-test completion status
- 11.2 UC 5.2 – Query system status and error information

12 IM-6 – Activate system's routines, input/output control(s)

- 12.1 UC 6.1 – Activate system's routine(s)
- 12.2 UC 6.2 – Activate system's input/output control(s)

13 Overview of vehicle system requirements

- 13.1 ePTI external test equipment and vehicle message exchange sequence
- 13.2 Technical requirements and use case coverage

14 Application (APP)

14.1 Setup vehicle's DoCAN data link framework
14.2 Setup vehicle's DoIP data link framework
14.3 Choice of DoCAN and DoIP data link in the vehicle

15 Application layer (AL)

15.1 Applicable ISO 14229-1 UDS functionality
15.2 Authentication
15.2.1 Requirements definition — ePTI external test equipment authentication
15.2.2 Requirements definition — ECU authentication
15.3 ReadDataByIdentifier — Report ePTI-relevant system(s)
15.3.1 Requirements definition — Report ePTI-relevant system(s)
15.3.2 Message sequence implementation requirements — Report ePTI-relevant system(s)
15.3.3 Example of the message sequence — Report ePTI-relevant system(s)
15.4 ReadDataByIdentifier — Report ECU supported data identifier(s)
15.4.1 Requirements definition — Report ECU supported data identifier(s)
15.4.2 Message sequence implementation requirements — Report ECU supported data identifier(s)
15.4.3 Example of the message sequence — Report ECU supported data identifier(s)
15.5 ReadDataByIdentifier — Report ECU supported routine identifier(s)
15.5.1 Requirements definition — Report ECU supported routine identifier(s)
15.5.2 Message sequence implementation requirements — Report ECU supported routine identifier(s)
15.5.3 Example of the message sequence — Report ECU supported routine identifier(s)
15.6 ReadDataByIdentifier — Report ECU supported input/output control identifier(s)
15.6.1 Requirements definition — Report ECU supported input/output control identifier(s)
15.6.2 Message sequence implementation requirements — Report ECU supported input/output control identifier(s)
15.6.3 Example of the message sequence — Report ECU supported input/output control identifier(s)
15.7 ReadDataByIdentifier — Report VIN from ECU
15.7.1 Requirements definition — Report VIN from ECU
15.7.2 Message sequence implementation requirements — Report VIN from ECU
15.7.3 Example of the message sequence — Report VIN from ECU
15.8 ReadDataByIdentifier — Report vehicle odometer value
15.8.1 Requirements definition — Report vehicle odometer value
15.8.2 Message sequence implementation requirements — Report vehicle odometer value
15.8.3 Example of the message sequence — Report vehicle odometer value
15.9 ReadDataByIdentifier — Report vehicle's system software number(s)
15.9.1 Requirements definition — Report vehicle's system software number(s)
15.9.2 Message sequence implementation requirements — Report vehicle's system software number(s)
15.10 ReadDataByIdentifier — Report information from system
15.10.1 Requirements definition — Report information from system
15.10.2 Message sequence implementation requirements — Report information from system
15.10.3 Example of the message sequence — Report information from system
15.11 ReadDataByIdentifier — Report vehicle's ePTI system self-test completion and system status
15.11.1 Requirements definition — Report vehicle's ePTI system self-test completion and system status
15.11.2 Message sequence implementation requirements — Report vehicle's ePTI system self-test completion and system status
15.11.3 Example of the message sequence — Report vehicle's ePTI system self-test completion and system status
15.12 RoutineControl — Activate system's routines
15.12.1 Requirements definition — Activate system's routines
15.12.2 Message sequence implementation requirements — Activate system's routines
15.12.3 Example of the message sequence — Activate system's routines exterior lights
15.13 InputOutputControlByIdentifier — Activate system's input/output controls
15.13.1 Requirements definition — Activate system's input/output controls
15.13.2 Message sequence implementation requirements — Activate system's input/output controls
15.13.3 Example of the message sequence — Activate system's input/output controls
16 Session layer (SL)

Page count: 42