# ISO 11992-3:2021 (E)

## Road vehicles — Interchange of digital information on electrical connections between towing and towed vehicles — Part 3: Application layer for equipment other than brakes and running gear

## Contents


Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Abbreviated terms

5 APP – Parameter specification

5.1 General definitions
5.2 Rear obstacle distance
5.3 Thermal body temperature
5.4 Obstacle detection device (ODD) request
5.5 Anti-theft device – Status request
5.6 Obstacle detection device (ODD) active
5.7 Anti-theft device – Measured
5.8 Vehicle type
5.9 Detailed vehicle type
5.10 Percent clutch slip
5.11 Current gear
5.12 Accelerator pedal low idle switch
5.13 Engine propulsion system control allowed
5.14 PTO control allowed
5.15 Tachograph vehicle speed
5.16 Engine propulsion system speed measured
5.17 Driver’s demand engine propulsion system – Percent torque
5.18 Actual engine propulsion system – Percent torque
5.19 Transmission reference torque
5.20 Engine propulsion system percent load at current speed
5.21 Maximum vehicle speed limit
5.22 Engine propulsion system speed upper limit
5.23 Engine propulsion system speed lower limit
5.24 Engine propulsion system coolant temperature warning
5.25 Engine propulsion system oil pressure warning
5.26 Engine propulsion system oil temperature
5.27 Engine propulsion system coolant temperature
5.28 Engine propulsion system oil pressure
5.29 Torque converter oil temperature warning
5.30 Torque converter oil temperature
5.31 First clutch-dependent PTO feedback
5.32 Second clutch-dependent PTO feedback
5.33 Clutch-independent PTO feedback
5.34 First engine propulsion system-mounted PTO feedback
5.35 Second engine propulsion system-mounted PTO feedback
5.36 Starter active
5.37 Engine propulsion system running
5.38 Engine propulsion system torque mode
5.39 First clutch-dependent PTO switch

| | |
|---|---|
| 5.40 | Second clutch-dependent PTO switch |
| 5.41 | Clutch-independent PTO switch |
| 5.42 | First engine propulsion system-mounted PTO switch |
| 5.43 | Second engine propulsion system-mounted PTO switch |
| 5.44 | Requested percent clutch slip |
| 5.45 | Starter lockout switch |
| 5.46 | Engine propulsion system start switch |
| 5.47 | Engine propulsion system stop switch |
| 5.48 | Requested engine propulsion system speed upper limit |
| 5.49 | Requested engine propulsion system speed lower limit |
| 5.50 | Requested engine propulsion system torque limit |
| 5.51 | Requested vehicle speed limit |
| 5.52 | Refuse packer step switch |
| 5.53 | Operating panel active |
| 5.54 | Requested engine propulsion system speed |
| 5.55 | Accelerator pedal position |
| 5.56 | Ambient air temperature |
| 5.57 | Fuel level warning |
| 5.58 | Towed vehicle left-hand stop light(s) |
| 5.59 | Towed vehicle right-hand stop light(s) |
| 5.60 | Towed vehicle left-hand direction indicator light(s) |
| 5.61 | Towed vehicle right-hand direction indicator light(s) |
| 5.62 | Towed vehicle left-hand rear light(s) |
| 5.63 | Towed vehicle right-hand rear position light(s) |
| 5.64 | Towed vehicle left-hand rear fog light(s) |
| 5.65 | Towed vehicle right-hand rear fog light(s) |
| 5.66 | Towed vehicle left-hand reversing light(s) |
| 5.67 | Towed vehicle right-hand reversing light(s) |
| 5.68 | Towed vehicle left-hand side marker light(s) |
| 5.69 | Towed vehicle right-hand side marker light(s) |
| 5.70 | Towed vehicle left-hand rear width indicator light(s) |
| 5.71 | Towed vehicle right-hand rear width indicator light(s) |
| 5.72 | Towed vehicle left-hand corner marker light(s) |
| 5.73 | Towed vehicle right-hand corner marker light(s) |
| 5.74 | Towed vehicle left-hand rear registration-plate light(s) |
| 5.75 | Towed vehicle right-hand rear registration-plate light(s) |
| 5.76 | Towed vehicle rear warning light(s) |
| 5.77 | Towed vehicle rotating identification light(s) |
| 5.78 | Towed vehicle interior light(s) |
| 5.79 | Towed vehicle work light(s) |
| 5.80 | Body fluid level |
| 5.81 | Actual pressure |
| 5.82 | Towed vehicle rear black-out marker select light(s) |
| 5.83 | Towed vehicle front black-out marker lamp select |
| 5.84 | Towed vehicle convoy lamp select |
| 5.85 | Towed vehicle convoy driving lamp select |
| 5.86 | Towed vehicle black-out brake/stop lamp select |
| 5.87 | Towed vehicle night vision illuminator select |
| 5.88 | Towed vehicle black-out work lamp select |
| 5.89 | Towed vehicle operators black-out intensity selection |
| 5.90 | Towed vehicle left hand black-out rear light(s) |
| 5.91 | Towed vehicle right-hand black-out rear light(s) |
| 5.92 | Towed vehicle left-hand black-out brake/stop light(s) |
| 5.93 | Towed vehicle right-hand black-out brake/stop light(s) |
| 5.94 | Towed vehicle rear convoy light(s) |
| 5.95 | ODM version information |
| 5.96 | Identification data index |
| 5.97 | Identification data content |
| 5.98 | Velocity and yaw rate confidence level |
| 5.99 | OD status indicator |
| 5.100 | Cyclic redundancy check (CRC8) |
| 5.101 | Sequence counter |
| 5.102 | Longitudinal speed |
| 5.103 | Lateral speed |

**5.104** Yaw rate
**5.105** Articulation angle
**5.106** OD longitudinal distance object
**5.107** OD lateral distance object
**5.108** OD absolute longitudinal speed object
**5.109** OD absolute lateral speed object
**5.110** OD standard deviation of longitudinal and lateral distance
**5.111** OD normal deviation of longitudinal and lateral speed
**5.112** Track ID
**5.113** Lane curve coefficients
**5.114** Lane curve validity interval
**5.115** Lane marker width
**5.116** Standard deviation of lane information error
**5.117** Lane marker type
**5.118** Object width (dimension in lateral direction)
**5.119** Object length (dimension in longitudinal direction)
**5.120** Object classification
**5.121** Geometric distance
**5.122** Towed vehicle rear IR-black-out marker select
**5.123** Towed vehicle IR-black-out stop lamp select
**5.124** Towed vehicle IR-convoy light ('Leitkreuz') select
**5.125** Towed vehicle right-hand IR-black-out rear light(s)
**5.126** Towed vehicle left-hand IR-black-out rear light(s)
**5.127** Towed vehicle right-hand IR-black-out stop light(s)
**5.128** Towed vehicle left-hand IR-black-out stop light(s)
**5.129** Towed vehicle IR-convoy light ('Leitkreuz')
**5.130** Towed vehicle black-out work lamp(s)
**5.131** Seconds
**5.132** Minutes
**5.133** Hours
**5.134** Day
**5.135** Month
**5.136** Year
**5.137** Local minute offset
**5.138** Local hour offset
**5.139** Trailer left-hand stop light(s)
**5.140** Trailer right-hand stop light(s)
**5.141** Trailer left-hand direction indicator light(s)
**5.142** Trailer right-hand direction indicator light(s)
**5.143** Trailer left-hand rear light(s)
**5.144** Trailer right-hand rear light(s)
**5.145** Trailer left-hand rear fog light(s)
**5.146** Trailer right-hand rear fog light(s)
**5.147** Trailer left-hand reversing light(s)
**5.148** Trailer right-hand reversing light(s)
**5.149** Trailer left-hand side marker light(s)
**5.150** Trailer right-hand side marker light(s)
**5.151** Trailer left-hand rear width indicator light(s)
**5.152** Trailer right-hand rear width indicator light(s)
**5.153** Trailer left-hand corner marker light(s)
**5.154** Trailer right-hand corner marker light(s)
**5.155** Trailer left-hand rear registration-plate light(s)
**5.156** Trailer right-hand rear registration-plate light(s)
**5.157** Trailer rear warning light(s)
**5.158** Trailer rotating identification light(s)
**5.159** Trailer interior light(s)
**5.160** Trailer work light(s)
**5.161** Trailer left-hand stop light(s) redundancy function
**5.162** Trailer right-hand stop light(s) redundancy function
**5.163** Trailer left-hand direction indicator light(s) redundancy function
**5.164** Trailer right-hand direction indicator light(s) redundancy function
**5.165** Trailer left-hand rear light(s) redundancy function
**5.166** Trailer right-hand rear light(s) redundancy function
**5.167** Trailer left-hand reversing light(s) redundancy function

5.168 Trailer right-hand reversing light(s) redundancy function
5.169 Transmission output shaft PTO feedback
5.170 Transfer case output shaft PTO feedback
5.171 At least one PTO engaged
5.172 Transmission output shaft PTO switch
5.173 Transfer case output shaft PTO switch
5.174 First clutch-dependent PTO engagement consent
5.175 Second clutch-dependent PTO engagement consent
5.176 Clutch-independent PTO engagement consent
5.177 First engine propulsion system mounted PTO engagement consent
5.178 Second engine propulsion system mounted PTO engagement consent
5.179 Transmission output shaft PTO engagement consent
5.180 Transfer case output shaft PTO engagement consent
5.181 First clutch-dependent PTO engagement consent – Trailer
5.182 Second clutch-dependent PTO engagement consent – Trailer
5.183 Clutch-independent PTO engagement consent – Trailer
5.184 First engine propulsion system mounted PTO engagement consent – Trailer
5.185 Second engine propulsion system mounted PTO engagement consent – Trailer
5.186 Transmission output shaft PTO engagement consent – Trailer
5.187 Transfer case output shaft PTO engagement consent – Trailer
5.188 Cargo hold temperature 1
5.189 Cargo hold temperature 2
5.190 Cargo hold temperature 3
5.191 Cargo hold temperature 4
5.192 Cargo hold temperature 5
5.193 Cargo hold temperature 6
5.194 Reefer unit battery voltage
5.195 Reefer unit fuel tank level
5.196 Requested evaporator 1 set-point
5.197 Requested evaporator 2 set-point
5.198 Requested evaporator 3 set-point
5.199 Evaporator 1 set-point
5.200 Evaporator 2 set-point
5.201 Evaporator 3 set-point
5.202 Compartment 1 humidity
5.203 Compartment 2 humidity
5.204 Compartment 3 humidity
5.205 Compartment 1 oxygen concentration
5.206 Compartment 2 oxygen concentration
5.207 Compartment 3 oxygen concentration
5.208 Reefer unit alarm status
5.209 Status evaporator 1
5.210 Status evaporator 2
5.211 Status evaporator 3
5.212 Reefer unit status
5.213 Reefer unit start/stop operating hours
5.214 Reefer unit diesel engine propulsion system operating hours
5.215 Reefer unit line supply operating hours
5.216 Reefer unit generator operating hours
5.217 Reefer unit on/off
5.218 Reefer unit defrost cycle on/off
5.219 Cargo hold door 1 contact switch
5.220 Cargo hold door 2 contact switch
5.221 Cargo hold door 3 contact switch

6 PG specification

6.1 Towing vehicle
6.1.1 General requirements
6.1.2 Overview of towing vehicle PGs
6.1.3 CANopen messages
6.1.4 General purpose message #1/1 (GPM11)
6.1.5 General purpose message #1/2 (GPM12)
6.1.6 General purpose message #1/3 (GPM13)
6.1.7 General purpose message #1/4 (GPM14)

6.1.8 General purpose message #1/5 (GPM15)
6.1.9 General purpose message #1/6 (GPM16)
6.1.10 General purpose message #1/7 (GPM17)
6.1.11 General purpose message #1/8 (GPM18)
6.1.12 General purpose message #1/9 (GPM19)
6.1.13 Military application message #1/1 (MAM11)
6.1.14 Time/Date message #1/1 (TD11)
6.1.15 Object detection message #1/1 (ODM11)
6.2 Towed vehicle
6.2.1 General requirements
6.2.2 Overview of towed vehicle messages
6.2.3 General purpose message #2/1 (GPM21)
6.2.4 General purpose message #2/2 (GPM22)
6.2.5 General purpose message #2/3 (GPM23)
6.2.6 General purpose message #2/4 (GPM24)
6.2.7 General purpose message #2/5 (GPM25)
6.2.8 General purpose message #2/6 (GPM26)
6.2.9 General purpose message #2/7 (GPM27)
6.2.10 General purpose message #2/8 (GPM28)
6.2.11 General purpose message #2/9 (GPM29)
6.2.12 General purpose message #2/10 (GPM210)
6.2.13 General purpose message #2/11 (GPM211)
6.2.14 Military application message #2/1 (MAM21)
6.2.15 Object detection message #2/1 (ODM21)
6.2.16 Object detection message #2/2 (ODM22)
6.2.17 Object detection message #2/3 (ODM23)
6.2.18 Object detection message #2/4 (ODM24)
6.2.19 Object detection message #2/5 (ODM25)
6.2.20 Object detection message #2/6 (ODM26)
6.2.21 Object detection message #2/7 (ODM27)
6.2.22 Object detection message #2/8 (ODM28)
6.2.23 Object detection message #2/9 (ODM29)
6.2.24 Object detection message #2/10 (ODM210)
6.2.25 Object detection message #2/11 (ODM211)
6.2.26 Object detection message #2/12 (ODM212)
6.2.27 Object detection message #2/13 (ODM213)
6.2.28 Object detection message #2/14 (ODM214)
6.2.29 Object detection message #2/15 (ODM215)
6.2.30 Object detection message #2/16 (ODM216)
6.2.31 Object detection message #2/17 (ODM217)
6.2.32 Object detection message #2/18 (ODM218)
6.2.33 Object detection message #2/19 (ODM219)
6.2.34 Object detection message #2/20 (ODM220)
6.2.35 Object detection message #2/21 (ODM221)

7 Application

7.1 General requirements
7.2 Address assignment
7.3 Address assignment method of a towing and towed vehicle
7.4 Vehicle node capabilities
7.5 Parameter attributes

8 AL – Application layer

8.1 AL – Message PDU format
8.2 AL – Message routing
8.3 AL – Parameter specification
8.3.1 AL – General
8.3.2 AL – Parameter attribute ranges

9 PL – Presentation layer

10 AL – ODM requirements

10.1 AL – Message latency
10.2 AL – Object selection

10.2.1 AL – General
10.2.2 AL – On the side of the vehicle
10.2.3 AL – Behind the vehicle
10.2.4 AL – Further objects
10.3 AL – Error handling

Annex A (informative) Object detection (OD) sensor states

A.1 States and transitions of the OD status sensor
A.2 Prioritisation of the detected objects in the ODM

Annex B (informative) Message flow

**Page count: 133**