

# ISO 21806-11:2021 (E)

## Road vehicles — Media Oriented Systems Transport (MOST) — Part 11: 150-Mbit/s coaxial physical layer conformance test plan

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
4.1	Symbols
4.2	Abbreviated terms
5	Conventions
6	Operating conditions and measurement tools, requested accuracy
6.1	Operating conditions
6.2	Apparatus — Measurement tools, requested accuracy
7	Electrical characteristics
7.1	Test according to LVDS
7.2	Test according to LVTTTL
8	Coaxial characteristics
8.1	High/low detection at SP2
8.2	Transition times at SP2
8.3	Steady state amplitude at SP2
8.4	Attenuation of coaxial interconnect
8.4.1	General
8.4.2	Coefficient values based on attenuation measurements
8.4.3	Fitting of corridor
8.4.4	Attenuation test set-up
8.4.5	Test procedure
8.4.5.1	General
8.4.5.2	Data acquisition
8.4.5.3	Data fitting
8.4.5.4	Attenuation conformance
8.4.5.5	Impact of attenuation on data signal
8.5	RL of connectors and couplers
8.6	Characteristic impedance of coaxial cable
8.7	RL of coaxial interconnect
8.8	RL of PCB interfaces
8.9	Stimulus creation for SP3
8.9.1	General
8.9.2	Pattern generator
8.9.3	Arbitrary signal generator
8.9.4	Attenuator
8.9.5	Cable or analogue representation
8.9.6	Noise generator
8.9.7	Creating a stimulus for SP3 for simplex applications
8.9.8	Creating a stimulus for SP3 for duplex applications

- 9           **Measurement of phase variation**
  - 9.1        **General**
  - 9.2        **Measuring alignment jitter**
  - 9.3        **Measuring transferred jitter**
- 10          **Test set-ups**
  - 10.1       **General**
  - 10.2       **Graphical symbols and descriptions**
    - 10.2.1     **Pattern generator SP1**
    - 10.2.2     **SP3 stimulus**
    - 10.2.3     **Standalone simplex ECport under test**
    - 10.2.4     **Integrated simplex ECport under test**
    - 10.2.5     **Standalone simplex CEport under test**
    - 10.2.6     **Integrated simplex CEport under test**
    - 10.2.7     **Duplex ECport under test**
    - 10.2.8     **Duplex CEport under test**
  - 10.3       **Set-ups for dual simplex**
    - 10.3.1     **General**
    - 10.3.2     **SP2 signal quality measurement for simplex**
    - 10.3.3     **SP4 jitter measurement (AJ and TJ) for simplex**
  - 10.4       **Set-ups for duplex**
    - 10.4.1     **General**
    - 10.4.2     **Directional couplers**
    - 10.4.3     **SP2 signal quality measurement for duplex**
    - 10.4.4     **SP4 jitter measurement (AJ and TJ) for duplex**
- 11          **Power-on and power-off**
  - 11.1       **General**
  - 11.2       **Measuring ECC parameters**
    - 11.2.1     **Measuring ECC parameters – Test set-up**
    - 11.2.2     **Measuring ECC parameters – Signal charts**
    - 11.2.3     **Measuring ECC parameters – Test sequences**
      - 11.2.3.1   **ECC test sequence #1 – off-state to on-state by SP1 signal**
      - 11.2.3.2   **ECC test sequence #2 – off-state to on-state by SP1 signal**
      - 11.2.3.3   **ECC test sequence #3 - on-state to off-state by SP1 signal**
      - 11.2.3.4   **ECC test sequence #4 - off-state to on-state by SP1 signal**
      - 11.2.3.5   **ECC test sequence #5 - on-state to off-state by SP1 signal**
      - 11.2.3.6   **ECC test sequence #6 - off-state to on-state by /RST signal**
      - 11.2.3.7   **ECC test sequence #7 - on-state to off-state by /RST signal**
  - 11.3       **Measuring CEC parameters**
    - 11.3.1     **Measuring CEC parameters – Test set-up**
    - 11.3.2     **Measuring CEC parameters – Signal charts**
    - 11.3.3     **Measuring CEC parameters – Test sequences**
      - 11.3.3.1   **General**
      - 11.3.3.2   **CEC test sequence #1 – off-state to on-state**
      - 11.3.3.3   **CEC test sequence #2 – off-state to on-state**
      - 11.3.3.4   **CEC test sequence #3 – off-state to on-state**
      - 11.3.3.5   **CEC test sequence #4 – off-state to on-state**
      - 11.3.3.6   **CEC test sequence #5 – on-state to off-state**
      - 11.3.3.7   **CEC test sequence #6 – off-state to on-state**
      - 11.3.3.8   **CEC test sequence #7 – on-state to off-state**
- 12          **Detecting bit rate (frequency reference)**
- 13          **System performance**
  - 13.1       **General**
  - 13.2       **SP4 receiver tolerance**
  - 13.3       **TimingMaster delay tolerance**
- 14          **Conformance tests of 150-Mbit/s coaxial physical layer**
  - 14.1       **Location of interfaces**
  - 14.2       **Control signals**
  - 14.3       **Limited access to specification points**

14.4	Parameter overview
15	Limited physical layer conformance
15.1	Overview
15.2	Test set-ups 1 and 2
15.3	Generating test signals for the IUT input section SP3
15.4	Analysis of test results
15.5	Test flow overview
15.6	Measurement of SP3 input signal of the IUT
15.7	Measurement of SP2 output signal of the IUT
15.8	Measurement of RL
15.9	Functional test of wake-up and shutdown
16	Direct physical measuring accuracy
17	Measurement of Port1 delay drift
Annex A	(informative) Limited physical layer conformance for development tools
Annex B	(normative) SP3 stress conditions
Annex C	(normative) Compensation set-up for MOST150 cPHY duplex
C.1	General
C.2	Compensation method for set-up related reflections
C.2.1	General
C.2.2	Scenario A – IUT as TimingSlave
C.2.2.1	General
C.2.2.2	Test operation
C.2.2.3	Reflection compensation
C.2.3	Scenario B – IUT as TimingMaster
C.2.3.1	General
C.2.3.2	Test operation
C.2.3.3	Reflection compensation
Annex D	(informative) Test procedure for 2-port nodes
D.1	Enhanced test set-ups for 2-port nodes
D.2	Enhanced test flow for 2-port nodes

Page count: 84