

ISO 22737:2021 (E)

Intelligent transport systems — Low-speed automated driving (LSAD) systems for predefined routes — Performance requirements, system requirements and performance test procedures

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
5	Example use case for an LSAD system deployment
6	LSAD system architecture
7	Basic requirements
7.1	General
7.2	Minimum operating capabilities
7.3	Operational design domains (ODDs)
7.4	LSAD state transition diagram
7.4.1	LSAD state functional descriptions
7.4.1.1	LSAD off
7.4.1.2	LSAD standby
7.4.1.3	LSAD active
7.4.2	LSAD state transition description:
7.4.2.1	A1
7.4.2.2	B1
7.4.2.3	B2
7.4.2.4	C1
7.4.2.5	C2
7.4.2.6	C3
7.4.2.7	C4
7.4.2.8	C5
7.4.2.9	C6
7.4.3	Possible extension of the LSAD state diagram to accommodate dispatcher inputs
7.4.3.1	Safe to proceed confirmation request
7.4.3.2	Safe to proceed confirmation authorization
7.4.3.3	Operating mode command
7.5	Communication requirements
8	Functional requirements
8.1	Determination of hazardous situation
8.1.1	General
8.1.2	Non-occluded view
8.1.3	Occluded view
8.2	Minimal risk manoeuvre (MRM)
8.3	Driving in the drivable area
8.4	Emergency stop (e-stop)
9	Performance requirements for the LSAD system
9.1	Maximum subject vehicle speed (VSV_max)

- 9.2 Obstacle detection requirements
 - 9.2.1 Maximum pedestrian speed (Vped_max)
 - 9.2.2 Maximum pedal cyclist speed (Vpc_max)
 - 9.2.3 LSAD system deceleration
- 10 System requirements
 - 10.1 Recording data about a safety-critical event
- 11 Performance test procedures
 - 11.1 General
 - 11.2 Environmental parameters
 - 11.3 Hazardous situation
 - 11.3.1 Pedestrian as an obstacle
 - 11.3.1.1 Test setup
 - 11.3.1.2 Vehicle parameters
 - 11.3.1.3 Pedestrian target parameters – Situation A
 - 11.3.1.4 Pedestrian and vehicle target parameters – Situation B
 - 11.3.1.5 Pedestrian target parameters – Situation C
 - 11.3.1.6 Longitudinal start distance
 - 11.3.1.7 Environmental parameters
 - 11.3.1.8 Pass criteria
 - 11.3.2 Pedal cyclist as an obstacle
 - 11.3.2.1 Test setup
 - 11.3.2.2 Vehicle parameters
 - 11.3.2.3 Pedal cyclist target parameters – Situation A
 - 11.3.2.4 Pedal cyclist and Vehicle Target Parameters – Situation B
 - 11.3.2.5 Pedal cyclist target parameters – Situation C
 - 11.3.2.6 Longitudinal start distance, Slong
 - 11.3.2.7 Environmental parameters
 - 11.3.2.8 Pass criteria
 - 11.3.3 Hazardous situation turning around a corner
 - 11.3.3.1 Test setup
 - 11.3.3.2 Vehicle parameters
 - 11.3.3.3 Pedestrian target parameters
 - 11.3.3.4 Longitudinal start distance (Slong)
 - 11.3.3.5 Lateral detection evaluation zone (Slat1)
 - 11.3.3.6 Environmental parameters
 - 11.3.3.7 Pass criteria
 - 11.3.4 False positive tests
 - 11.3.4.1 Test setup
 - 11.3.4.2 Vehicle parameters
 - 11.3.4.3 Pedestrian target parameters – Situation A, Figure 12 a)
 - 11.3.4.4 Pedestrian target parameters – Situation B, Figure 12 b)
 - 11.3.4.5 Longitudinal distance (Slong)
 - 11.3.4.6 Environmental parameters
 - 11.3.4.7 Pass criteria
 - 11.4 Drivable area test
 - 11.4.1 Test setup
 - 11.4.2 Vehicle parameters
 - 11.4.3 Evaluation path parameters
 - 11.4.4 Environmental parameters
 - 11.4.5 Pass criteria for unblocked drivable area
 - 11.4.6 Pass criteria for blocked drivable area
 - 11.5 Minimal risk manoeuvre (MRM) test
 - 11.5.1 Test setup
 - 11.5.2 Vehicle parameters
 - 11.5.3 Evaluation path parameters
 - 11.5.4 Environmental parameters
 - 11.5.5 MRM trigger
 - 11.5.6 Pass criteria

Annex A (informative) Test speeds for hazardous situation tests

Annex B (informative) Example LSAD communication messages

Annex C (informative) Example LSAD system data recorder

Annex D (informative) LSAD system activities (experiment tests) in various countries

- D.1 Japan
- D.2 United States
- D.3 United Kingdom
- D.4 Europe
- D.5 Australia
- D.6 Taiwan

Page count: 43