

ISO 15765-4:2021-07 (E)

Road vehicles - Diagnostic communication over Controller Area Network (DoCAN) - Part 4: Requirements for emissions-related systems

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and abbreviated terms	2
4.1	Symbols	2
4.2	Abbreviated terms	3
5	Conventions	4
6	Application	4
6.1	Vehicle communication initialisation sequence	4
6.1.1	OBDonUDS protocol identification	4
6.1.2	OBDonEDS protocol identification	4
6.1.3	Others	4
6.2	External test equipment communication initialisation sequence	4
6.3	Bit rate validation procedure	5
6.3.1	bitrateRecord	5
6.3.2	Bit rate validation	5
6.3.3	External test equipment error detection provisions	6
6.4	CAN identifier validation procedure	7
6.4.1	CAN identifier validation procedure OBDonEDS	7
6.4.2	CAN identifier validation procedure OBDonUDS	9
6.5	Support of ECUNAME reporting	11
7	Application layer (AL)	11
8	Session layer (SL)	12
9	Transport layer (TL)	12
10	Network layer (NL)	12
10.1	General	12
10.2	Parameter definitions	12
10.2.1	Timing parameter values	12
10.2.2	Definition of flow control parameter values	13
10.2.3	Maximum number of OBDonUDS or OBDonEDS ECUs	14
10.3	Addressing formats	15
10.3.1	Normal and normal fixed addressing format	15
10.3.2	Functional addressing	15
10.3.3	Physical addressing	15
10.4	CAN identifier requirements	16
10.4.1	External test equipment	16
10.4.2	OBDonUDS or OBDonEDS server/ECU	16
10.5	Mapping of diagnostic addresses	16

10.5.1	OBDonUDS/OBDonEDS CAN identifiers	16
10.5.2	11-bit CAN identifiers	17
10.5.3	29-bit CAN identifiers	18
11	Data link layer (DLL)	18
12	Physical layer (PHY)	18
12.1	General	18
12.2	Bit rates	19
12.3	CAN bit timing	19
12.3.1	Parameter values	19
12.3.2	Nominal bit rate 250 kbit/s	20
12.3.3	Nominal bit rate 500 kbit/s	20
12.4	External test equipment	21
12.4.1	Electrical parameters	21
12.4.2	Cable parameters	24
	Bibliography	25