

ISO 6622-1:2021 (E)

Internal combustion engines — Piston rings — Part 1: Rectangular rings made of cast iron

Contents

| | |
|-------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Overview |
| 5 | Ring types and designation examples |
| 5.1 | Overview |
| 5.2 | Type R — Straight faced rectangular ring |
| 5.2.1 | General features |
| 5.2.2 | Designation |
| 5.3 | Type B — Barrel faced rectangular ring |
| 5.3.1 | General features |
| 5.3.2 | Designation |
| 5.4 | Type BA — Asymmetrical barrel faced rectangular ring $h_1 \geq 1,2$ mm |
| 5.4.1 | General features |
| 5.4.2 | Designation |
| 5.5 | Type M — Taper faced rectangular ring |
| 5.5.1 | General features |
| 5.5.2 | Designation |
| 6 | Common features |
| 6.1 | Face coating types |
| 6.2 | Face shape types |
| 6.3 | Piston ring twist features |
| 6.3.1 | Taper faced rectangular ring with partly cylindrical machined (LM) or lapped (LP) peripheral surface |
| 6.4 | Chamfered edges |
| 6.5 | Type R, B, BA and M rings (fully faced, semi-inlaid and inlaid) — Plating/coating thickness |
| 6.6 | Type R, B, BA, and M rings — Nitrided case depth |
| 7 | Force factors |
| 8 | Dimensions |

Page count: 26