

ISO 15765-5:2021-09 (E)

Road vehicles - Diagnostic communication over Controller Area Network (DoCAN) - Part 5: Specification for an in-vehicle network connected to the diagnostic link connector

| Contents | | Page |
|------------------------------|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Symbols and abbreviated terms | 1 |
| 4.1 | Symbols | 1 |
| 4.2 | Abbreviated terms | 2 |
| 5 | Conventions | 3 |
| 6 | In-vehicle network to external test equipment connection | 3 |
| 6.1 | Connectivity scenarios between external test equipment and vehicle | 3 |
| 6.2 | Technical requirements overview | 3 |
| 6.3 | SI -- Data.req, Data.ind and Data.conf service interface | 4 |
| 6.4 | SI -- Parameter mapping and configuration of OSI-layers | 5 |
| 6.5 | Transport layer (TL) | 5 |
| 6.5.1 | TL - Data interface primitive parameter mapping | 5 |
| 6.5.2 | TL - Message segmentation | 6 |
| 6.5.3 | TL ISO 15765-2 packet flow control | 6 |
| 6.6 | Network layer (NL) | 6 |
| 6.6.1 | NL - Data interface primitive parameter mapping | 6 |
| 6.6.2 | NL - ISO 15765-2 network layer services | 7 |
| 6.6.3 | NL - ISO 15765-2 network layer timing parameters | 7 |
| 6.6.4 | NL - ISO 15765-2 uniqueness of node diagnostic address | 7 |
| 6.6.5 | NL - ISO 15765-2 supported addressing formats | 7 |
| 6.7 | Data link layer (DLL) | 8 |
| 6.7.1 | DLL - Data interface primitive parameter mapping | 8 |
| 6.7.2 | DLL - Service interface parameter requirements | 9 |
| 6.7.3 | DLL - Device acceptance of CAN identifier | 10 |
| 6.8 | Physical layer (PHY) | 10 |
| 6.8.1 | PHY - Physical signalling (PS) requirements | 10 |
| 6.8.2 | PHY - Physical medium attachment (PMA) requirements | 14 |
| 6.8.3 | PHY - Physical media dependent (PMD) sub-layer requirements | 14 |
| Annex A (informative) | Compatibility between test equipment and in-vehicle network connected to diagnostic link connector | 16 |
| Bibliography | | 17 |