

ISO 15765-5:2021-09 (E)

Road vehicles - Diagnostic communication over Controller Area Network (DoCAN) - Part 5: Specification for an in-vehicle network connected to the diagnostic link connector

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	1
4.1 Symbols	1
4.2 Abbreviated terms	2
5 Conventions	3
6 In-vehicle network to external test equipment connection	3
6.1 Connectivity scenarios between external test equipment and vehicle	3
6.2 Technical requirements overview	3
6.3 SI -- Data.req, Data.ind and Data.conf service interface	4
6.4 SI -- Parameter mapping and configuration of OSI-layers	5
6.5 Transport layer (TL)	5
6.5.1 TL - Data interface primitive parameter mapping	5
6.5.2 TL - Message segmentation	6
6.5.3 TL ISO 15765-2 packet flow control	6
6.6 Network layer (NL)	6
6.6.1 NL - Data interface primitive parameter mapping	6
6.6.2 NL - ISO 15765-2 network layer services	7
6.6.3 NL - ISO 15765-2 network layer timing parameters	7
6.6.4 NL - ISO 15765-2 uniqueness of node diagnostic address	7
6.6.5 NL - ISO 15765-2 supported addressing formats	7
6.7 Data link layer (DLL)	8
6.7.1 DLL - Data interface primitive parameter mapping	8
6.7.2 DLL - Service interface parameter requirements	9
6.7.3 DLL - Device acceptance of CAN identifier	10
6.8 Physical layer (PHY)	10
6.8.1 PHY - Physical signalling (PS) requirements	10
6.8.2 PHY - Physical medium attachment (PMA) requirements	14
6.8.3 PHY - Physical media dependent (PMD) sub-layer requirements	14
Annex A (informative) Compatibility between test equipment and in-vehicle network connected to diagnostic link connector	16
Bibliography	17