

DIN 4630:2022-05 (E)

Road vehicles - Data parameter specification for body application units in commercial vehicles; Text in English

Inhalt	Seite
Foreword	6
1 Scope.....	7
2 Normative references	7
3 Terms and definitions.....	8
4 Abbreviations	9
5 Definition of use cases	10
5.1 General use cases	10
5.2 Examples of network-architecture	11
5.3 BAU sub-parts.....	11
6 Specification of parameters	12
6.1 Parameter attributes.....	12
6.2 Detailed specification of generic parameters	12
6.2.1 General.....	12
6.2.2 Error code	12
6.2.3 Alarm code.....	13
6.2.4 Commercial vehicle status.....	13
6.2.5 Vehicle lowering status	14
6.2.6 Vehicle load	14
6.3 Detailed specification of general ECU parameters	15
6.3.1 General.....	15
6.3.2 ECU input voltage	15
6.3.3 ECU temperature	15
6.3.4 CPU temperature	15
6.3.5 Hosting vehicle type	16
6.3.6 Implemented logical entities	16
6.4 Detailed specification of TGU parameters.....	17
6.4.1 General.....	17
6.4.2 BAU or sub-part enable request	17
6.5 Detailed specification of IGU parameters.....	18
6.5.1 General.....	18
6.5.2 ISO 11992 parameters	18
6.5.3 CiA 413-5 parameters	18
6.5.4 J1939 parameters.....	18
6.6 Detailed specification of the FMU parameters.....	18
6.7 Detailed specification of general BAU parameters.....	18
6.7.1 General.....	18
6.7.2 BAU type.....	18
6.7.3 BAU sub-type.....	19
6.7.4 Next maintenance day.....	19
6.7.5 Next maintenance month.....	19
6.7.6 Next maintenance year.....	20
6.8 Detailed specification of generic BAU and BAU sub-part parameters	20
6.8.1 General.....	20
6.8.2 BAU or BAU sub-part.....	20
6.8.3 BAU or BAU sub-part mode	21

6.8.4	BAU or sub-part mounting location	21
6.8.5	BAU or sub-part status.....	22
6.8.6	BAU or sub-part enable status	22
6.8.7	BAU or sub-part position status	23
6.8.8	BAU or sub-part moving status	23
6.8.9	Operating hours.....	24
6.8.10	Resettable operating hours.....	24
6.8.11	Operating cycles	24
6.8.12	Resettable operating cycles	25
6.8.13	Remaining operating hours	25
6.8.14	Hydraulic oil pressure	26
6.8.15	Hydraulic oil level	26
6.8.16	Hydraulic oil temperature.....	26
6.8.17	Chain emergency-stop status	27
6.8.18	Windshield wiper control request.....	27
7	Specification of BAU specific parameters.....	28
7.1	General	28
7.2	Lifting units (LU).....	28
7.2.1	General	28
7.2.2	LU categories	28
7.2.3	Transport position status	28
7.2.4	Vehicle-mounted crane unit (VMCU)	29
7.2.5	Tail-lift unit (TLU)	29
7.3	Heating and refrigerating unit (HRU).....	33
7.3.1	General	33
7.3.2	HRU classes	34
7.3.3	HRU compartment number	34
7.3.4	HRU temperature setpoint command.....	34
7.3.5	HRU return air temperature.....	35
7.3.6	HRU supply air temperature	35
7.3.7	HRU evaporator temperature	35
7.3.8	HRU compartment temperature setpoint status	35
7.3.9	HRU status	36
7.3.10	HRU ambient temperature.....	36
7.3.11	HRU battery voltage	37
7.3.12	HRU diesel operating hours.....	37
7.3.13	HRU electrical operating hours	37
7.3.14	HRU total operating hours	38
7.3.15	HRU functionality and mode.....	38
7.4	Refuse collecting unit (RCU)	39
7.4.1	General	39
7.4.2	RCU categories.....	39
7.4.3	Classes of RCU compliant to EN 16815	40
7.5	Container unit (CU).....	41
7.5.1	General	41
7.5.2	Categories of CUs	41
7.5.3	General CU parameters	42
7.5.4	CU status.....	42
7.5.5	Closure elements states	43
7.6	Tipper unit (TU)	44
7.6.1	General	44
7.6.2	Categories of TUs.....	44
7.6.3	Temperature of loaded material.....	44
7.6.4	Tipper inclination in x-axis.....	44
7.6.5	Tipper inclination in y-axis.....	45
7.7	Fire-fighting unit (FFU)	45
7.7.1	General	45

7.7.2	Categories of FFUs	45
7.7.3	Specific FFU parameters.....	45
Annex A	(normative) Parameter mapping to SAE J1939-based networks	46
A.1	Mapping of the application layer.....	46
A.1.1	General.....	46
A.1.2	Industry group and source addresses	46
A.1.3	Overview on general PGs	46
A.1.4	Overview on PGs transmitted by LUs.....	51
A.1.5	Overview on PGs transmitted by HRUs	51
A.1.6	Overview on PGs transmitted by RCUs.....	52
A.1.7	Overview on PGs f transmitted by CUs	52
A.1.8	Overview on PGs transmitted by TUs	52
A.1.9	Overview on PGs transmitted by FFUs.....	52
A.2	Detailed specification of general PGs.....	52
A.2.1	Alarms (ALARM)	52
A.2.2	Acoustic warning request (AWR).....	52
A.2.3	Acoustic warning state (AWS)	53
A.2.4	Vehicle load (AXL).....	53
A.2.5	Body application unit 1 (BAU1)	54
A.2.6	Body application unit 2 (BAU2)	55
A.2.7	Body application unit 3 (BAU3)	55
A.2.8	Body application unit 4 (BAU4)	56
A.2.9	Body application unit 5 (BAU5)	56
A.2.10	Body application unit 6 (BAU6)	57
A.2.11	Body application unit 7 (BAU7)	58
A.2.12	Body application unit 8 (BAU8)	58
A.2.13	Electronic control unit (ECU).....	59
A.2.14	ECU power supply (ECU_PWR)	59
A.2.15	ECU temperatures (ECU_TMP).....	60
A.2.16	Error information (ERROR)	60
A.2.17	Heating and refrigerating unit 1 (HRU1).....	61
A.2.18	Heating and refrigerating unit 2 (HRU2).....	62
A.2.19	Heating and refrigerating unit 3 (HRU3).....	62
A.2.20	Heating and refrigerating unit 4 (HRU4).....	63
A.2.21	HRU temperature setpoint (HTS).....	63
A.2.22	Lifting unit (LU1)	64
A.2.23	Tail-lift unit 1 (TLU1)	65
A.2.24	Vehicle status (VS)	65
A.2.25	Windshield wiper request (WWR).....	66
A.3	Transport layer protocol specification	66
A.4	Data link layer protocol requirements.....	66
A.5	Physical layer requirements.....	67
A.5.1	General requirements.....	67
A.5.2	Connector requirements.....	67
A.6	Additional requirements	67
A.6.1	Address claiming	67
A.6.2	Sleep and wake-up handling.....	68
Annex B	(normative) Parameter mapping to EN 50325-4 (CANopen) communication networks	69
B.1	CANopen specific parameter attributes.....	69
B.2	Mapping to the application layer	69
B.2.1	Overview	69
B.2.2	Pre-specified PDOs.....	71
B.3	Transport layer protocol requirements	71
B.4	Data link layer protocol requirements.....	71
B.5	Physical layer requirements.....	71
Annex C	(informative) Begriffe.....	72
	Bibliography.....	74