DIN 4630:2022-05 (E)

Road vehicles - Data parameter specification for body application units in commercial vehicles; Text in English

Inhalt

Seite

Foreword 6

1 Scope 7

2 Normative references 7

3 Terms and definitions 8

4 Abbreviations 9

5 Definition of use cases 10
5.1 General use cases 10
5.2 Examples of network-architecture 11
5.3 BAU sub-parts 11

6 Specification of parameters 12
6.1 Parameter attributes 12
6.2 Detailed specification of generic parameters 12
6.2.1 General 12
6.2.2 Error code 12
6.2.3 Alarm code 13
6.2.4 Commercial vehicle status 13
6.2.5 Vehicle lowering status 14
6.2.6 Vehicle load 14
6.3 Detailed specification of general ECU parameters 15
6.3.1 General 15
6.3.2 ECU input voltage 15
6.3.3 ECU temperature 15
6.3.4 CPU temperature 15
6.3.5 Hosting vehicle type 16
6.3.6 Implemented logical entities 16
6.4 Detailed specification of TGU parameters 17
6.4.1 General 17
6.4.2 BAU or sub-part enable request 17
6.5 Detailed specification of IGU parameters 18
6.5.1 General 18
6.5.2 ISO 11992 parameters 18
6.5.3 CiA 413-5 parameters 18
6.5.4 J1939 parameters 18
6.6 Detailed specification of the FMU parameters 18
6.7 Detailed specification of general BAU parameters 18
6.7.1 General 18
6.7.2 BAU type 18
6.7.3 BAU sub-type 19
6.7.4 Next maintenance day 19
6.7.5 Next maintenance month 19
6.7.6 Next maintenance year 20
6.8 Detailed specification of generic BAU and BAU sub-part parameters 20
6.8.1 General 20
6.8.2 BAU or BAU sub-part 20
6.8.3 BAU or BAU sub-part mode 21

6.8.4 BAU or sub-part mounting location 21
6.8.5 BAU or sub-part status 22
6.8.6 BAU or sub-part enable status 22
6.8.7 BAU or sub-part position status 23
6.8.8 BAU or sub-part moving status 23
6.8.9 Operating hours 24
6.8.10 Resettable operating hours 24
6.8.11 Operating cycles 24
6.8.12 Resettable operating cycles 25
6.8.13 Remaining operating hours 25
6.8.14 Hydraulic oil pressure 26
6.8.15 Hydraulic oil level 26
6.8.16 Hydraulic oil temperature 26
6.8.17 Chain emergency-stop status 27
6.8.18 Windshield wiper control request 27

7 Specification of BAU specific parameters 28
7.1 General 28
7.2 Lifting units (LU) 28
7.2.1 General 28
7.2.2 LU categories 28
7.2.3 Transport position status 28
7.2.4 Vehicle-mounted crane unit (VMCU) 29
7.2.5 Tail-lift unit (TLU) 29
7.3 Heating and refrigerating unit (HRU) 33
7.3.1 General 33
7.3.2 HRU classes 34
7.3.3 HRU compartment number 34
7.3.4 HRU temperature setpoint command 34
7.3.5 HRU return air temperature 35
7.3.6 HRU supply air temperature 35
7.3.7 HRU evaporator temperature 35
7.3.8 HRU compartment temperature setpoint status 35
7.3.9 HRU status 36
7.3.10 HRU ambient temperature 36
7.3.11 HRU battery voltage 37
7.3.12 HRU diesel operating hours 37
7.3.13 HRU electrical operating hours 37
7.3.14 HRU total operating hours 38
7.3.15 HRU functionality and mode 38
7.4 Refuse collecting unit (RCU) 39
7.4.1 General 39
7.4.2 RCU categories 39
7.4.3 Classes of RCU compliant to EN 16815 40
7.5 Container unit (CU) 41
7.5.1 General 41
7.5.2 Categories of CUs 41
7.5.3 General CU parameters 42
7.5.4 CU status 42
7.5.5 Closure elements states 43
7.6 Tipper unit (TU) 44
7.6.1 General 44
7.6.2 Categories of TUs 44
7.6.3 Temperature of loaded material 44
7.6.4 Tipper inclination in x-axis 44
7.6.5 Tipper inclination in y-axis 45
7.7 Fire-fighting unit (FFU) 45
7.7.1 General 45

7.7.2 Categories of FFUs 45
7.7.3 Specific FFU parameters 45

Annex A (normative) Parameter mapping to SAE J1939-based networks 46
A.1 Mapping of the application layer 46
A.1.1 General 46
A.1.2 Industry group and source addresses 46
A.1.3 Overview on general PGs 46
A.1.4 Overview on PGs transmitted by LUs 51
A.1.5 Overview on PGs transmitted by HRUs 51
A.1.6 Overview on PGs transmitted by RCUs 52
A.1.7 Overview on PGs f transmitted by CUs 52
A.1.8 Overview on PGs transmitted by TUs 52
A.1.9 Overview on PGs transmitted by FFUs 52
A.2 Detailed specification of general PGs 52
A.2.1 Alarms (ALARM) 52
A.2.2 Acoustic warning request (AWR) 52
A.2.3 Acoustic warning state (AWS) 53
A.2.4 Vehicle load (AXL) 53
A.2.5 Body application unit 1 (BAU1) 54
A.2.6 Body application unit 2 (BAU2) 55
A.2.7 Body application unit 3 (BAU3) 55
A.2.8 Body application unit 4 (BAU4) 56
A.2.9 Body application unit 5 (BAU5) 56
A.2.10 Body application unit 6 (BAU6) 57
A.2.11 Body application unit 7 (BAU7) 58
A.2.12 Body application unit 8 (BAU8) 58
A.2.13 Electronic control unit (ECU) 59
A.2.14 ECU power supply (ECU_PWR) 59
A.2.15 ECU temperatures (ECU_TMP) 60
A.2.16 Error information (ERROR) 60
A.2.17 Heating and refrigerating unit 1 (HRU1) 61
A.2.18 Heating and refrigerating unit 2 (HRU2) 62
A.2.19 Heating and refrigerating unit 3 (HRU3) 62
A.2.20 Heating and refrigerating unit 4 (HRU4) 63
A.2.21 HRU temperature setpoint (HTS) 63
A.2.22 Lifting unit (LU1) 64
A.2.23 Tail-lift unit 1 (TLU1) 65
A.2.24 Vehicle status (VS) 65
A.2.25 Windshield wiper request (WWR) 66
A.3 Transport layer protocol specification 66
A.4 Data link layer protocol requirements 66
A.5 Physical layer requirements 67
A.5.1 General requirements 67
A.5.2 Connector requirements 67
A.6 Additional requirements 67
A.6.1 Address claiming 67
A.6.2 Sleep and wake-up handling 68

Annex B (normative) Parameter mapping to EN 50325-4 (CANopen) communication networks 69
B.1 CANopen specific parameter attributes 69
B.2 Mapping to the application layer 69
B.2.1 Overview 69
B.2.2 Pre-specified PDOs 71
B.3 Transport layer protocol requirements 71
B.4 Data link layer protocol requirements 71
B.5 Physical layer requirements 71

Annex C (informative) Begriffe 72

Bibliography 74