

# ISO 16844-4:2022-02 (E)

## Road vehicles - Tachograph systems - Part 4: Display unit communication interface

<b>Contents</b>	<b>Page</b>
Foreword.....	iv
Introduction.....	v
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Symbols and abbreviated terms</b> .....	<b>2</b>
<b>5 CAN physical layer requirements</b> .....	<b>3</b>
5.1 General.....	3
5.2 CAN bit-timing requirements.....	3
5.2.1 General.....	3
5.2.2 CAN bit-timing requirements for 250 kbit/s.....	3
5.2.3 CAN bit-timing requirements for 500 kbit/s.....	4
<b>6 CAN data link layer requirements</b> .....	<b>4</b>
<b>7 Transport layer requirements</b> .....	<b>4</b>
<b>8 Application layer</b> .....	<b>4</b>
8.1 General requirements and permissions.....	4
8.2 RQST — Request message.....	5
8.3 ACKM — Acknowledgement message.....	5
8.4 TD — Time/date.....	6
8.5 VI — Vehicle identification.....	6
8.6 VDHR — High-resolution vehicle distance.....	6
8.7 SERV — Service information.....	6
8.8 RESET — Reset.....	6
8.9 TCO1 — Tachograph.....	7
8.10 DI — Driver's identification.....	7
8.11 TDA — Time/date adjust.....	8
8.12 EEC1 — Electronic engine controller 1.....	8
<b>9 Optional parameter groups</b> .....	<b>9</b>
9.1 CL — Cab illumination message.....	9
9.2 Driving and rest times driver 1/2 - DRTD1/2.....	9
9.2.1 DRTD1 — Driver 1 driving rest times.....	9
9.2.2 DRTD2 — Driver 2 driving rest times.....	10
<b>10 Recommended source address (SA) assignments</b> .....	<b>10</b>
<b>Bibliography</b> .....	<b>12</b>