

DIN EN 16062:2023-10 (E)

Intelligent transport systems - ESafety - eCall high level application requirements (HLAP) using GSM/UMTS circuit switched networks

Contents		Page
European foreword		4
Introduction		5
1	Scope	7
2	Normative references	7
3	Terms and definitions	8
4	Symbols and abbreviations	11
5	Conformance	12
6	General overview of the eCall transaction for Pan European eCall	14
7	Requirements	18
7.1	General requirements	18
7.1.1	General	18
7.1.2	USIM	18
7.1.3	Enabled PSAP	18
7.1.4	IVS configured only for eCall	18
7.1.5	Self-test	19
7.1.6	Standby mode applicable to IVS configured for eCall only	19
7.2	Activation	19
7.2.1	Activation of pan-European eCall	19
7.2.2	Activation of a test eCall	20
7.3	Call set-up	20
7.3.1	General	20
7.3.2	IVS network access device (NAD) already registered on PLMN	20
7.3.3	eCall in progress	20
7.3.4	Network selection and registration	20
7.3.5	Authentication of the subscriber	21
7.3.6	eCall establishment	21
7.3.7	Cell localization (by network)	21
7.3.8	Manual termination of eCall by vehicle occupants before trigger confirmation	22
7.4	MSD transfer	22
7.4.1	General	22
7.4.2	Send initiation signal from IVS eCall modem to PSAP	23
7.4.3	eCall modem synchronization	23
7.4.4	Request MSD by PSAP eCall modem to IVS eCall modem	24
7.4.5	Send MSD from vehicle IVS to PSAP eCall modem	24
7.4.6	Link layer error check	24
7.4.7	Link layer ACK from PSAP eCall modem to IVS eCall modem	24
7.5	Application layer acknowledgement (AL- ACK)	25
7.5.1	Following transmission of the MSD to the eCall PSAP application	25
7.5.2	PSAP acknowledges the MSD	25
7.5.3	No receipt of application layer ACK	25
7.5.4	Form of presentation of the AL-ACK	25
7.6	PSAP request "SEND MSD"	27
7.6.1	General	27

7.6.2	Before call clear-down	27
7.6.3	After call clear-down	29
7.7	(void)	29
7.8	Audio link to vehicle occupants	29
7.9	eCall clear-down	29
7.10	PSAP call back	30
7.11	Rerouting to another PSAP/emergency control centre	30
7.12	Handling non equipped situations / error cases	31
7.12.1	MSD not transmitted correctly	31
7.12.2	Network registration fails	31
7.12.3	Call failure before the MSD is sent and acknowledged	31
7.12.4	Mobile network not supporting eCall flag or not provided with routing tables	31
7.12.5	PSAP modem failure	32
7.12.6	PSAP network/ICT failure	32
7.12.7	PSAP application failure	32
7.12.8	PSAP operator does not respond	32
7.12.9	No response if line engaged	33
7.12.10	MSD not sent	33
7.12.11	MSD not received	33
7.12.12	Audio link not established	33
7.12.13	Audio link established but subsequently fails	34
7.12.14	Re-attempt in case of interrupted call	34
7.12.15	Automatic repeat attempts	34
7.12.16	IVS NAD does not receive call clear-down	34
8	Third party services supported eCall (TPS-eCall)	34
9	Defences against attack (Security provisions)	35
10	Quality of service requirements	35
11	Test and conformance requirements	35
12	Marking, labelling and packaging	35
13	Declaration of patents and intellectual property	35
Annex A (normative) Table of timings		36
Annex B (informative) (void)		39
Annex C (informative) Test system strategies		40
C.1	General	40
C.2	Vehicle and PSAP equipment life cycle	40
C.3	Laboratory environment	41
C.4	OEM or third party test systems	41
Bibliography		43