

ISO 14229-3:2022-03 (E)

Road vehicles - Unified diagnostic services (UDS) - Part 3: Unified diagnostic services on CAN implementation (UDSonCAN)

Contents	Page
Foreword.....	v
Introduction.....	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	1
4.1 Symbols.....	1
4.2 Abbreviated terms.....	2
5 Conventions	2
6 Service primitive interface definition	3
7 Technical requirements overview	3
8 Application layer	4
8.1 ISO 14229-1 service primitive parameters.....	4
8.2 A_Data.req, A_Data.ind, and A_Data.conf service interface.....	4
8.3 UDSonCAN services overview.....	4
8.4 A_PDU definition.....	5
8.5 ReadDataByPeriodicIdentifier service UDSonCAN implementation requirements.....	6
8.5.1 UUDT periodic transmission response message handling.....	6
8.5.2 Service interface - UUDT.....	6
8.5.3 UUDT service primitive parameters.....	8
8.5.4 UUDT message format.....	9
8.5.5 Periodic transmission message flow.....	10
8.6 Timing parameter definition.....	13
8.6.1 Request and response message timing parameter values.....	13
8.6.2 Unsolicited response messages.....	13
9 Presentation layer	13
10 Session layer	13
10.1 Service primitive parameter definition.....	13
10.2 S_Data.req, S_Data.ind, and S_Data.conf service interface.....	13
11 Transport layer	14
11.1 USDT service primitive parameters.....	14
11.2 T_Data.req, T_Data.ind, and T_Data.conf service interface.....	14
11.3 Transport protocol.....	14
11.4 T_PDU definition.....	14
11.5 DoCAN transport and network layer interface adaptation.....	14
11.5.1 Mapping of data link independent service primitives onto CAN data link-dependent service primitives.....	14
11.5.2 Mapping of T_PDU onto N_PDU.....	15
12 Network layer	15
12.1 Service primitive parameter definition.....	15
12.2 N_Data.req, N_Data.ind, and N_Data.conf service interface.....	15
12.3 Network layer services.....	16
12.4 N_PDU definition.....	16
12.5 N_TAtype service primitive parameter.....	16
12.6 Same N_TAtype request and associated response message format.....	16

13	Data link layer	17
13.1	Service primitive parameter definition	17
13.2	L_Data.req, L_Data.ind, and L_Data.conf service interface	17
13.3	Usage of ISO 15765-4-defined 11-bit CAN identifiers for enhanced diagnostics	17
13.4	Usage of ISO 15765-4-defined 29-bit CAN identifiers for enhanced diagnostics	18
14	Physical layer	18
	Bibliography	19