

ISO 14229-3:2022-03 (E)

Road vehicles - Unified diagnostic services (UDS) - Part 3: Unified diagnostic services on CAN implementation (UDSonCAN)

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and abbreviated terms	1
4.1	Symbols	1
4.2	Abbreviated terms	2
5	Conventions	2
6	Service primitive interface definition	3
7	Technical requirements overview	3
8	Application layer	4
8.1	ISO 14229-1 service primitive parameters	4
8.2	A_Data.req, A_Data.ind, and A_Data.conf service interface	4
8.3	UDSonCAN services overview	4
8.4	A_PDU definition	5
8.5	ReadDataByPeriodicIdentifier service UDSonCAN implementation requirements	6
8.5.1	UUDT periodic transmission response message handling	6
8.5.2	Service interface - UUDT	6
8.5.3	UUDT service primitive parameters	8
8.5.4	UUDT message format	9
8.5.5	Periodic transmission message flow	10
8.6	Timing parameter definition	13
8.6.1	Request and response message timing parameter values	13
8.6.2	Unsolicited response messages	13
9	Presentation layer	13
10	Session layer	13
10.1	Service primitive parameter definition	13
10.2	S_Data.req, S_Data.ind, and S_Data.conf service interface	13
11	Transport layer	14
11.1	USDT service primitive parameters	14
11.2	T_Data.req, T_Data.ind, and T_Data.conf service interface	14
11.3	Transport protocol	14
11.4	T_PDU definition	14
11.5	DoCAN transport and network layer interface adaptation	14
11.5.1	Mapping of data link independent service primitives onto CAN data link-dependent service primitives	14
11.5.2	Mapping of T_PDU onto N_PDU	15
12	Network layer	15
12.1	Service primitive parameter definition	15
12.2	N_Data.req, N_Data.ind, and N_Data.conf service interface	15
12.3	Network layer services	16
12.4	N_PDU definition	16
12.5	N_TAtype service primitive parameter	16
12.6	Same N_TAtype request and associated response message format	16

13	Data link layer	17
13.1	Service primitive parameter definition	17
13.2	L_Data.req, L_Data.ind, and L_Data.conf service interface	17
13.3	Usage of ISO 15765-4-defined 11-bit CAN identifiers for enhanced diagnostics	17
13.4	Usage of ISO 15765-4-defined 29-bit CAN identifiers for enhanced diagnostics	18
14	Physical layer	18
	Bibliography	19