ISO 14229-3:2022-03 (E)

Road vehicles - Unified diagnostic services (UDS) - Part 3: Unified diagnostic services on CAN implementation (UDSonCAN)

Contents

Page

Foreword ..... **v**

Introduction ..... **vi**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Symbols and abbreviated terms **1**
4.1 Symbols 1
4.2 Abbreviated terms 2

5 Conventions **2**

6 Service primitive interface definition **3**

7 Technical requirements overview **3**

8 Application layer **4**
8.1 ISO 14229-1 service primitive parameters 4
8.2 A_Data.req, A_Data.ind, and A_Data.conf service interface 4
8.3 UDSonCAN services overview 4
8.4 A_PDU definition 5
8.5 ReadDataByPeriodicIdentifier service UDSonCAN implementation requirements 6
8.5.1 UUDT periodic transmission response message handling 6
8.5.2 Service interface – UUDT 6
8.5.3 UUDT service primitive parameters 8
8.5.4 UUDT message format 9
8.5.5 Periodic transmission message flow 10
8.6 Timing parameter definition 13
8.6.1 Request and response message timing parameter values 13
8.6.2 Unsolicited response messages 13

9 Presentation layer **13**

10 Session layer **13**
10.1 Service primitive parameter definition 13
10.2 S_Data.req, S_Data.ind, and S_Data.conf service interface 13

11 Transport layer **14**
11.1 USDT service primitive parameters 14
11.2 T_Data.req, T_Data.ind, and T_Data.conf service interface 14
11.3 Transport protocol 14
11.4 T_PDU definition 14
11.5 DoCAN transport and network layer interface adaptation 14
11.5.1 Mapping of data link independent service primitives onto CAN data link-dependent service primitives 14
11.5.2 Mapping of T_PDU onto N_PDU 15

12 Network layer **15**
12.1 Service primitive parameter definition 15
12.2 N_Data.req, N_Data.ind, and N_Data.conf service interface 15
12.3 Network layer services 16
12.4 N_PDU definition 16
12.5 N_TAtype service primitive parameter 16
12.6 Same N_TAtype request and associated response message format 16

13 Data link layer **17**
13.1 Service primitive parameter definition 17
13.2 L_Data.req, L_Data.ind, and L_Data.conf service interface 17
13.3 Usage of ISO 15765-4-defined 11-bit CAN identifiers for enhanced diagnostics 17
13.4 Usage of ISO 15765-4-defined 29-bit CAN identifiers for enhanced diagnostics 18
14 Physical layer **18**
Bibliography **19**