

ISO 15118-20:2022-04 (E)

Road vehicles - Vehicle to grid communication interface - Part 20: 2nd generation network layer and application layer requirements

Contents		Page
Foreword		v
Introduction		vi
1 Scope		1
2 Normative references		1
3 Terms and definitions		4
4 Abbreviated terms		12
5 Conventions		15
5.1 Definition of OSI based services		15
5.2 Requirement structure		15
5.3 Usage of references		16
5.4 Notation used for XML schema diagrams		16
6 Document overview		16
7 Basic requirements for V2G communication		17
7.1 General information		17
7.2 Service primitive concept of OSI layered architecture		18
Overview 18		
Syntax of service primitives		18
7.3 Security concept		19
General		19
Certificate and key management		21
Number of root certificates and root validity		35
Support and application of TLS		37
Firewall 38		
Protection of the cryptographic keys		38
Random number generation		40
7.4 V2G communication states and data link handling		42
7.5 Data link layer		46
Data link layer security for WLAN		46
7.6 Network link layer		51
General		51
Applicable RFCs, limitations and protocol parameter settings		51

IP addressing	53
7.7 Transport layer	54
Transmission control protocol (TCP)	54
User datagram protocol (UDP)	55
Transport layer security (TLS)	56
7.8 V2G transfer protocol	82
General information	82
Supported ports	83
Protocol data unit	84
7.9 Presentation layer	87
XML and efficient XML interchange (EXI)	87
Message security	90
7.10 Application layer	115
SECC discovery protocol	115
8 Application layer messages	128
8.1 General information and definitions	128
8.2 Protocol handshake definition	129
Handshake sequence	129
Message definition supportedAppProtocolReq and supportedAppProtocolRes	131
Semantics description supportedAppProtocol messages	132
Message examples	133
8.3 V2G message definition	134
Overview 134	
General	135
Header definition	135
Request and response definitions	138
Complex data types	240
8.4 Service selection	361
General	361
General description of configuration parameters	362
Selection of service and service parameters	363
8.5 V2G communication timing	373
Overview 373	
Common	373
DC service	374

Message sequence and communication session	374
Session setup and ready to charge	381
V2G message synchronization for AC and DC with IEC 61851-1 signalling	387
V2G message synchronization with IEC 61980-2 signalling for WPT	394
8.6 Message sequencing and error handling	394
Overview	394
Basic definitions for error handling	395
ResponseCode handling	395
Request-response message sequence requirements	406
Multiplexed communication	434
Message sequence diagrams	437
(normative) Schema definition	442
(normative) Certificate profiles	444
(normative) Specification of identifiers	498
(informative) ACDP	504
(informative) Basic PPD for interoperability	506
(informative) Message sequencing for renegotiation	509
(informative) Association of VAS client to V2G session	511
(informative) Application of certificates	512
(informative) Precision of measurements and tolerances	547
(informative) Absolute pricing examples	549