

ISO 14229-7:2022-04 (E)

Road vehicles - Unified diagnostic services (UDS) - Part 7: UDS on local interconnect network (UDSonLIN)

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Symbols and abbreviated terms | 2 |
| 4.1 | Symbols | 2 |
| 4.2 | Abbreviated terms | 2 |
| 5 | Conventions | 2 |
| 6 | Service primitive interface definition | 2 |
| 7 | Technical requirements | 3 |
| 7.1 | Overview | 3 |
| 7.2 | Implementation guidelines | 4 |
| 7.2.1 | General | 4 |
| 7.2.2 | Definition of diagnostic classes | 4 |
| 7.2.3 | LIN node requirements | 5 |
| 7.2.4 | Signal-based diagnostics | 6 |
| 7.2.5 | Tool suite support | 7 |
| 8 | Application layer | 7 |
| 8.1 | ISO 14229-1 service primitive parameters | 7 |
| 8.2 | A_Data.req, A_Data.ind, and A_Data.conf service interface | 7 |
| 8.3 | UDSonLIN services overview | 7 |
| 8.4 | A_PDU definition | 9 |
| 8.5 | A_Length definition | 9 |
| 8.6 | CommunicationControl service UDSonLIN implementation requirements | 9 |
| 8.7 | ResponseOnEvent service UDSonLIN implementation requirements | 10 |
| 8.8 | Timing parameter definition | 10 |
| 9 | Presentation layer | 12 |
| 10 | Session layer | 12 |
| 10.1 | Service primitive parameter definition | 12 |
| 10.2 | S_Data.req, S_Data.ind, and S_Data.conf service interface | 12 |
| 11 | Transport layer | 12 |
| 11.1 | General | 12 |
| 11.2 | Service primitive parameters | 12 |
| 11.3 | T_Data.req, T_Data.ind, and T_Data.conf service interface | 12 |
| 11.4 | T_PDU definition | 13 |
| 11.5 | LIN transport and network layer interface adaptation | 13 |
| 11.5.1 | Mapping of data link independent service primitives onto LIN data link-dependent service primitives | 13 |

| | | |
|--------|---|----|
| 11.5.2 | Mapping of T_PDU onto N_PDU | 13 |
| 12 | Network layer | 14 |
| 12.1 | Service primitive parameter definition | 14 |
| 12.2 | N_Data.req, N_Data.ind, and N_Data.conf service interface | 14 |
| 12.3 | N_PDU definition | 14 |
| 12.4 | N_TAtype service primitive parameter | 15 |
| 12.5 | LIN responder node requirements | 15 |
| 12.6 | LIN commander node requirements | 16 |
| 12.6.1 | Network address requirements | 16 |
| 12.6.2 | Use of functional addressing | 16 |
| 13 | Data link layer | 16 |
| 13.1 | Service primitive parameter definition | 16 |
| 13.2 | L_Data.req, L_Data.ind, and L_Data.conf service interface | 16 |
| 13.3 | L_PDU definition | 17 |
| 13.4 | L_PID definition | 17 |
| 13.5 | L_CS definition | 17 |
| 14 | Physical layer | 17 |
| | Bibliography | 18 |