

# ISO 23365:2022-07 (E)

## Heavy commercial vehicles and buses - Definitions of properties for the determination of suspension kinematic and compliance characteristics

Contents		Page
Foreword		vi
Introduction		vii
<b>1</b>	<b>Scope</b>	<b>1</b>
<b>2</b>	<b>Normative references</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions</b>	<b>1</b>
<b>4</b>	<b>Principle</b>	<b>4</b>
<b>5</b>	<b>Variables</b>	<b>5</b>
5.1	Reference system	5
5.2	Variables to be determined	5
5.2.1	Vehicle geometry	5
5.2.2	Motion variables	5
5.2.3	Forces and moments	5
5.2.4	Steering geometry	6
5.2.5	Kinematics	6
5.2.6	Compliances	7
5.2.7	Ride and roll stiffness	7
5.2.8	Force reactions	8
<b>6</b>	<b>Measuring equipment</b>	<b>8</b>
6.1	Measurement accuracy	8
6.2	Derived variable accuracy	9
<b>7</b>	<b>Suspension parameter measurement guidance</b>	<b>9</b>
7.1	Steering geometry	9
7.1.1	Steering ratio	9
7.1.2	Overall steering ratio ( $i_S$ )	10
7.1.3	Ackermann error	11
7.1.4	Inclination angle ( $\varepsilon_W$ )	11
7.1.5	Camber angle ( $\varepsilon_V$ )	11
7.1.6	Castor angle ( $\tau$ )	11
7.1.7	Castor offset at ground ( $n_k$ )	11
7.1.8	Castor offset at wheel centre ( $n_T$ )	12
7.1.9	Steering-axis inclination angle ( $\sigma$ )	12
7.1.10	Steering-axis offset at ground ( $r_k$ )	12
7.1.11	Steering-axis offset at wheel centre ( $r_\sigma$ )	12
7.1.12	Normal steering-axis offset at ground ( $q_T$ )	13
7.1.13	Normal steering axis offset at wheel centre ( $q_W$ )	13
7.1.14	Scrub radius ( $r$ )	13
7.2	Kinematics	14
7.2.1	General	14
7.2.2	Ride track change ( $b_z$ )	15
7.2.3	Ride track change gradient ( $b_z'$ )	15
7.2.4	Ride steer ( $\delta_z$ )	16
7.2.5	Ride steer gradient ( $\delta_z'$ )	16
7.2.6	Total ride toe ( $\delta_{z(R-L)}$ )	16
7.2.7	Total ride toe gradient ( $\delta_{z(R-L)'}'$ )	16
7.2.8	Ride camber ( $\varepsilon_{Vz}$ )	16
7.2.9	Ride camber gradient ( $\varepsilon_{Vz}'$ )	16
7.2.10	Ride castor ( $\tau_z$ )	17
7.2.11	Ride castor gradient ( $\tau_z'$ )	17
7.2.12	Roll steer ( $\delta_{\varphi_V}$ )	17

	7.2.13	Roll steer gradient ( $\delta_{\phi_V}$ )	17
	7.2.14	Roll camber ( $\epsilon_{V\phi_V}$ )	17
	7.2.15	Roll camber gradient ( $\epsilon_{V\phi_V}$ )	17
7.3		Compliances	18
	7.3.1	General	18
	7.3.2	Longitudinal force compliance, with suspension torque ( $x_{\bar{F}_X}$ )	18
	7.3.3	Longitudinal force compliance, without suspension torque ( $x_{\bar{F}_{XW}}$ )	19
	7.3.4	Longitudinal force camber compliance, with suspension torque ( $\epsilon_{V\bar{F}_X}$ )	19
	7.3.5	Longitudinal force camber compliance, without suspension torque ( $\epsilon_{V\bar{F}_{XW}}$ )	19
	7.3.6	Longitudinal force steer compliance, with suspension torque ( $\delta_{\bar{F}_X}$ )	20
	7.3.7	Longitudinal force steer compliance, without suspension torque ( $\delta_{\bar{F}_{XW}}$ )	20
	7.3.8	Longitudinal force windup compliance, with suspension torque ( $\tau_{\bar{F}_X}$ )	20
	7.3.9	Longitudinal force windup compliance, without suspension torque ( $\tau_{\bar{F}_{XW}}$ )	20
	7.3.10	Lateral force compliance at the wheel centre ( $y_{\bar{F}_{YW}}$ )	21
	7.3.11	Lateral force compliance at the contact centre ( $y_{\bar{F}_Y}$ )	21
	7.3.12	Lateral force camber compliance ( $\epsilon_{V\bar{F}_Y}$ )	21
	7.3.13	Lateral force steer compliance ( $\delta_{\bar{F}_Y}$ )	21
	7.3.14	Aligning moment camber compliance ( $\epsilon_{V\bar{M}_Z}$ )	22
	7.3.15	Aligning moment steer compliance ( $\delta_{\bar{M}_Z}$ )	22
7.4		Ride and roll stiffness	22
	7.4.1	General	22
	7.4.2	Ride rate ( $K_Z$ )	22
	7.4.3	Suspension ride rate ( $K_{ZK}$ )	23
	7.4.4	Roll stiffness ( $K_{\phi_V}$ )	23
	7.4.5	Suspension roll stiffness ( $K_{\phi_K}$ )	23
	7.4.6	Auxiliary roll stiffness ( $K_{\phi_V,aux}$ )	24
	7.4.7	Auxiliary suspension roll stiffness ( $K_{\phi_K,aux}$ )	24
	7.4.8	Vertical displacement tandem axle load redistribution stiffness ( $K_{tz}$ )	24
	7.4.9	Vertical suspension displacement tandem axle load redistribution stiffness ( $K_{tzK}$ )	25
	7.4.10	Tandem axle twist stiffness ( $K_{\phi_t}$ )	25
	7.4.11	Tandem axle suspension twist stiffness ( $K_{\phi_tK}$ )	25
	7.4.12	Tyre normal stiffness ( $K_{ZT}$ )	25
7.5		Force reactions	25
	7.5.1	Anti-squat and anti-dive force gradient ( $\bar{F}_{Z\bar{F}_X}$ )	25

7.5.2	Jacking force gradient ( $\bar{F}_{Z\bar{F}_Y}'$ ).....	26
7.5.3	Longitudinal force tandem axle load redistribution gradient ( $W_{Dt\bar{F}_{XT}}'$ ).....	26
<b>8</b>	<b>Data presentation</b> .....	<b>26</b>
8.1	Steering ratio .....	26
8.2	Kinematic properties .....	30
8.3	Compliance properties .....	31
8.4	Ride and roll stiffness properties .....	32
8.5	Force reaction properties .....	32
<b>Annex A (informative) Mathematic fit of steering ratio as a function of steering wheel angle</b> .....		<b>34</b>
<b>Bibliography</b> .....		<b>35</b>