ISO 15500-13:2023-02 (E)

Road vehicles - Compressed natural gas (CNG) fuel system components - Part 13: Pressure relief device (PRD)

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Marking 3

5 Construction and assembly 3

6 Tests 4
6.1 Applicability 4
6.2 Hydrostatic strength 4
6.2.1 Housing 4
6.2.2 Fusible material 5
6.3 Leakage 5
6.4 Bending moment 5
6.5 Continued operation 6
6.5.1 Test procedure 6
6.5.2 Requirements 6
6.6 Accelerated life 6
6.6.1 General 6
6.6.2 Test procedure 6
6.6.3 Accelerated-life test temperature 6
6.6.4 Requirements 7
6.7 Benchtop activation 7
6.7.1 General 7
6.7.2 Thermally-activated relief devices 7
6.7.3 Series-combination relief devices 7
6.7.4 Parallel-combination relief devices 8
6.8 Thermal cycling 8
6.8.1 Test procedure 8
6.8.2 Requirements 8
6.9 Condensate-corrosion resistance 9
6.9.1 Test procedure 9
6.9.2 Test solution 9
6.10 Flow capacity 9
6.10.1 General 9
6.10.2 Test procedure 9
6.11 High-pressure activation and flow rate 10
6.11.1 General 10
6.11.2 Test setup 10
6.11.3 Test procedure 10
6.11.4 Acceptable results 10
6.11.5 Data analysis and availability 10
6.12 Water jet protection 10
6.12.1 General 10

6.12.2 Method of test 10
6.12.3 Acceptance criteria 10
6.13 Impact due to drop 11

7 Production batch inspection and acceptance testing 11

Annex A (normative) Determination of fusible material yieldtemperature and PRD activation temperature 12

Bibliography 14