

ISO 15500-13:2023-02 (E)

Road vehicles - Compressed natural gas (CNG) fuel system components - Part 13: Pressure relief device (PRD)

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Marking	3
5	Construction and assembly	3
6	Tests	4
6.1	Applicability	4
6.2	Hydrostatic strength	4
6.2.1	Housing	4
6.2.2	Fusible material	5
6.3	Leakage	5
6.4	Bending moment	5
6.5	Continued operation	6
6.5.1	Test procedure	6
6.5.2	Requirements	6
6.6	Accelerated life	6
6.6.1	General	6
6.6.2	Test procedure	6
6.6.3	Accelerated-life test temperature	6
6.6.4	Requirements	7
6.7	Benchtop activation	7
6.7.1	General	7
6.7.2	Thermally-activated relief devices	7
6.7.3	Series-combination relief devices	7
6.7.4	Parallel-combination relief devices	8
6.8	Thermal cycling	8
6.8.1	Test procedure	8
6.8.2	Requirements	8
6.9	Condensate-corrosion resistance	9
6.9.1	Test procedure	9
6.9.2	Test solution	9
6.10	Flow capacity	9
6.10.1	General	9
6.10.2	Test procedure	9
6.11	High-pressure activation and flow rate	10
6.11.1	General	10
6.11.2	Test setup	10
6.11.3	Test procedure	10
6.11.4	Acceptable results	10
6.11.5	Data analysis and availability	10
6.12	Water jet protection	10
6.12.1	General	10

6.12.2	Method of test	10
6.12.3	Acceptance criteria	10
6.13	Impact due to drop	11
7	Production batch inspection and acceptance testing	11
Annex A (normative) Determination of fusible material yieldtemperature and PRD activation temperature		12
Bibliography		14