ISO 11992-4:2023-04 (E)

Road vehicles - Interchange of digital information on electrical connections between towing and towed vehicles - Part 4: Diagnostic communication

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Symbols and abbreviated terms 2
4.1 Symbols 2
4.2 Abbreviated terms 2

5 Conventions 2

6 Vehicle network architecture 3

7 Non OSI-layer-related technical requirements overview 4

8 Abstractserviceprimitiveinterface(ASP)definition 5
8.1 ASP - A_Data.req, A_Data.ind, and A_Data.con service primitive interface 5
8.2 ASP - Service interface parameters 6
8.2.1 General 6
8.2.2 ASP - Data type definitions 7
8.2.3 ASP - Mtype, message type 7
8.2.4 ASP - TAtype, target address type 7
8.2.5 ASP - AE, address extension 7
8.2.6 ASP - TA, target address 7
8.2.7 ASP - SA, source address 7
8.2.8 ASP - Length, length of PDU 8
8.2.9 ASP - PDU, protocol data unit 8
8.2.10 ASP - Result, result 8

9 Application 8
9.1 APP - Addressing of requested information 8
9.2 APP - Data identifier (DID) definition 8
9.3 APP - DTC field definition 9
9.4 APP - DTC functional unit definition 9
9.5 APP - Negative response code (NRC) 10
9.6 APP - Communication profile (ComProfile) 10

10 OSI-layers-related technical requirements overview 11

11 Application layer 12
11.1 AL - Diagnostic services overview 12
11.2 AL - CommunicationControl 13
11.3 AL - ReadDataByIdentifier 13
11.4 AL - ReadDtcInformation 14
11.4.1 AL - General 14
11.4.2 AL - Applicable ReadDtcInformation service subFunctions 14

11.5 AL - Application layer communication profile (ComProfile) 14

12 Presentation layer 14

13 Session layer 14
13.1 SL - Service primitive interface parameter definition 14
13.2 SL - S_Data.req, S_Data.ind, and S_Data.con service interface 14
13.3 SL - Service primitive interface AL to SL parameter mapping 15
13.4 SL - Session layer communication profile (ComProfile) 15

14 Transport layer 15
14.1 TL - USDT service primitive interface parameter definition 15
14.2 TL - T_Data.req, T_Data.ind, and T_Data.con service interface 15
14.3 TL - Service primitive interface SL to TL parameter mapping 16
14.4 TL - Transport protocol 16
14.5 TL - Transport layer communication profile (ComProfile) 16

15 Network layer 16
15.1 NL - Service primitive interface parameter definition 16
15.2 NL - N_Data.req, N_Data.ind, and N_Data.con service interface 17
15.3 NL - Service primitive interface TL to NL parameter mapping 17
15.4 NL - Network layer services 17
15.5 NL - Network layer communication profile (ComProfile) 17
15.6 NL - Diagnostic CAN identifier configuration 18
15.7 NL - Dynamic network address assignment 19
15.7.1 NL - General 19
15.7.2 NL - Address assignment of TTN_1 and TTN_3 19
15.7.3 NL - Address assignment of TTN_2 and TTN_4 20
15.8 NL - Static network address assignment 20
15.8.1 NL - General 20
15.8.2 NL - Address assignment of gateway application, IVN_1, and IVN_2 20
15.8.3 NL - Server address assignment of IVN_1 and IVN_2 20
15.9 NL - Gateway N_PDU routing 20
15.9.1 NL - General 20
15.9.2 NL - Network address translation 21
15.10 NL - Diagnostic communication port (DCP) 25

16 Data link layer 25
16.1 DL - Service primitive interface parameter definition 25
16.2 DL - L_Data.req, L_Data.ind, and L_Data.con service interface 25
16.3 DL - Service primitive interface NL to DL parameter mapping 26
16.4 DL - CAN data frame 26
16.5 DL - Data link layer communication profile (ComProfile) 26

17 Physical layer 26

Annex A (normative) Network address assignment 28

Bibliography 30