

ISO 11451-5:2023-05 (E)

Road vehicles - Vehicle test methods for electrical disturbances from narrowband radiated electromagnetic energy - Part 5: Reverberation chamber

| Contents | | Page |
|-----------------------|---|-------------|
| Foreword | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Test conditions | 6 |
| 5 | Test location | 6 |
| 5.1 | Reverberation chamber description | 6 |
| 5.2 | Working volume | 7 |
| 6 | Test instrumentation | 7 |
| 6.1 | General | 7 |
| 6.2 | Field generating device | 8 |
| 6.3 | Field probes | 8 |
| 6.4 | Stimulation and monitoring of the device under test (DUT) | 8 |
| 6.5 | Optional: receiving antenna(s) and spectrum analyser | 8 |
| 6.6 | Optional: vector network analyser | 9 |
| 7 | Test set-up | 9 |
| 7.1 | Vehicle placement | 10 |
| 7.2 | Field generating device location - Antenna constraints | 10 |
| 7.3 | Vehicle test configurations | 10 |
| 7.3.1 | Vehicle not connected to the power grid | 10 |
| 7.3.2 | Vehicle in charging mode 1 or mode 2 (AC powered, without communication) | 10 |
| 7.3.3 | Vehicle in charging mode 3 or mode 4 (AC or DC powered, with communication) | 13 |
| 7.3.4 | Vehicle in charging mode through wireless power transmission (WPT) | 17 |
| 8 | Test procedure | 19 |
| 8.1 | General | 19 |
| 8.2 | Stirring configurations | 20 |
| 8.3 | Test plan | 20 |
| 8.4 | Test methods | 20 |
| 8.5 | Reverb method with substitution method power control | 23 |
| 8.5.1 | Reverb reference points | 23 |
| 8.5.2 | Substitution method with empty chamber calibration | 25 |
| 8.5.3 | Substitution method with calibration including the vehicle | 29 |
| 8.6 | Test report | 31 |
| Annex A (informative) | Function performance status classification | 32 |
| Annex B (normative) | Test level definition | 33 |
| Annex C (normative) | Reverberation chamber characteristics | 36 |
| Annex D (informative) | Tuned mode and stirred mode | 44 |
| Annex E (informative) | TLS method | 48 |

| | |
|---|-----------|
| Annex F (informative) Cavity mode method | 55 |
| Annex G (informative) Reverb method with closed-loop power control | 59 |
| Annex H (informative) Chamber time constant method | 61 |
| Annex I (informative) VNA method | 67 |
| Annex J (informative) Measurement of total antenna efficiency | 74 |
| Annex K (informative) Measurement of diffuse field correction factor F_{df} | 77 |
| Annex L (informative) Measurement of σ, Q, and ACS | 80 |
| Annex M (normative) Additional AAN(s) | 85 |
| Bibliography | 86 |