

# ISO 22574:2023-08 (E)

## Road vehicles - Brake linings friction materials - Visual inspection

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Characteristic features for friction materials .....</b>	<b>1</b>
4.1	Characteristic features for disc brake pads .....	1
4.1.1	Gapping between material and plate .....	1
4.1.2	Edge chipping .....	2
4.1.3	Splits .....	2
4.1.4	Minor splits .....	3
4.1.5	Plucked and indented spigots .....	3
4.1.6	Poor consolidated spigot holes .....	3
4.1.7	Excess adhesive on plate .....	4
4.1.8	Material flash on plate .....	4
4.1.9	Abrasive coating .....	5
4.1.10	Anti-noise coating runs .....	5
4.1.11	Skin crazing .....	6
4.1.12	Underlayer distribution .....	6
4.1.13	Marking .....	7
4.1.14	Unground material surface .....	7
4.1.15	Paint on friction material surface .....	7
4.1.16	Surface blisters .....	8
4.1.17	Surface indentations .....	8
4.1.18	Grinding marks on friction surface .....	9
4.1.19	High porosity area .....	9
4.1.20	Poorly consolidated friction material .....	10
4.1.21	Surface contamination with foreign matters .....	10
4.1.22	Surface contamination with similar friction materials .....	11
4.1.23	Friction surface structure .....	11
4.1.24	Plate scratched and dents .....	12
4.1.25	Blanking burrs .....	12
4.1.26	Deformation by blanking and edge chipping at functional area .....	13
4.1.27	Edge shipping at pin area .....	13
4.1.28	Pinholes (Side-cut cavity) .....	14
4.1.29	Grinding marks on the carrier .....	14
4.1.30	Spring holder defects .....	15
4.1.31	Surface deepening .....	15
4.1.32	Cold laps .....	16
4.2	Characteristic features for drum brake linings .....	16
4.2.1	Chipped edges/corners .....	16
4.2.2	Edge splits .....	17
4.2.3	Drill hole chipping at lining ends .....	18
4.2.4	Drill hole burrs inside the surface .....	18
4.2.5	Drill hole burrs outside the surface .....	18
4.2.6	Cracks radiating from the rivet hole .....	19
4.2.7	Paint on surface - Lining for riveting and bonding .....	19

4.2.8	Surface cracks .....	20
4.2.9	Marking .....	20
4.2.10	Moulding skin on inside radius surface - linings for bonding and riveting .....	21
4.2.11	Moulding skin on outside radius surface - linings for riveting or bonding .....	21
4.2.12	Surface blisters .....	22
4.2.13	Surface grind marks .....	22
4.2.14	Pitted surface (plucked surface) .....	23
4.2.15	Surface structure .....	23
4.2.16	Poor consolidated friction material .....	24
4.2.17	Inside surface indentations .....	24
4.2.18	Outside surface indentations .....	25
4.2.19	Concentration of self-contained ingredients unless typical of the formulation .....	26
4.2.20	High porosity area .....	27
4.2.21	Metal wire or plastic reinforcement .....	27
4.2.22	Foreign matter friction surface inclusion .....	28
4.3	Characteristic features for bonded lined shoes .....	28
4.3.1	Lining overhang on shoe platform edge .....	28
4.3.2	Faulty shoes .....	29
4.3.3	Restricted lever movement .....	29
4.3.4	Stencilled information .....	30
4.3.5	Excess adhesive exudation over shoe platform edges .....	31
4.3.6	Excess adhesive exudation from lining ends .....	31
4.3.7	Excess primer .....	32
4.3.8	Lining surface condition .....	32
4.3.9	Gaps between linings and shoe platform .....	34