

DIN EN 17905:2024-02 (E)

Intelligent transport systems - eSafety - eCall HLAP in hybrid circuit switched/packet switched network environments

Contents		Page
European foreword		3
Introduction		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	6
4	Symbols and abbreviations	9
5	Conformance	9
6	General overview of the eCall session for Pan European eCall	10
7	Requirements	11
7.1	General	11
7.2	General requirements	11
7.2.1	Enabled IVS	11
7.2.2	Enabled PSAP	12
7.3	Procedures following power-up of the in-vehicle system: self-test	12
7.4	Activation	13
7.5	Call setup (IVS)	13
7.5.1	General	13
7.5.2	eCall activation	13
7.5.3	eCall in progress	13
7.5.4	Domain selection	13
7.5.5	Fallback	15
7.5.6	Domain handover	15
7.6	PSAP application features	16
7.6.1	General	16
7.6.2	Logging of MSD transfer type	16
7.6.3	MSD (update) request	16
7.6.4	Information to operator about hybrid situation	17
7.7	Handling non equipped situations / error cases	17
7.7.1	Network registration fails	17
7.7.2	Other issues	17
8	Third party services supported eCall (TPS-eCall)	17
9	Defences against attack (Security provisions)	17
10	Quality of service requirements	17
11	Test and conformance requirements	17
12	Marking, labelling and packaging	18
13	Declaration of patents and intellectual property	18

Annex A (informative) Transitional Use Cases	19
Bibliography	21