

ISO 15765-5:2023-11 (E)

Road vehicles - Diagnostic communication over Controller Area Network (DoCAN) -
Part 5: Specification for an in-vehicle network connected to the diagnostic link
connector

Contents

| | Page |
|---|------|
| Foreword | iv |
| Introduction | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 1 |
| 4 Symbols and abbreviated terms | 2 |
| 4.1 Symbols | 2 |
| 4.2 Abbreviated terms | 2 |
| 5 Conventions | 4 |
| 6 In-vehicle network to external test equipment connection | 4 |
| 6.1 Connectivity scenarios between external test equipment and vehicle | 4 |
| 6.2 Technical requirements overview | 4 |
| 6.3 ASP -- Data.req, Data.ind and Data.conf service interface | 5 |
| 6.4 ASP -- Parameter mapping and configuration of OSI layers | 5 |
| 6.5 Transport layer (TL) | 6 |
| 6.5.1 TL - Data interface primitive parameter mapping | 6 |
| 6.5.2 TL - Message segmentation | 6 |
| 6.5.3 TL - ISO 15765-2 segment flow control | 6 |
| 6.6 Network layer (NL) | 6 |
| 6.6.1 NL - Data interface primitive parameter mapping | 6 |
| 6.6.2 NL - ISO 15765-2 network layer services | 7 |
| 6.6.3 NL - ISO 15765-2 network layer timing parameters | 7 |
| 6.6.4 NL - ISO 15765-2 uniqueness of node diagnostic address | 7 |
| 6.6.5 NL - ISO 15765-2 supported addressing formats | 7 |
| 6.7 Data link layer (DLL) | 8 |
| 6.7.1 DLL - Data interface primitive parameter mapping | 8 |
| 6.7.2 DLL - Service interface parameter requirements | 9 |
| 6.7.3 DLL - Device acceptance of CAN identifier | 10 |
| 6.8 Physical layer (PHY) | 10 |
| 6.8.1 PHY - Classical CAN | 10 |
| 6.8.2 PHY - CAN FD | 12 |
| 6.8.3 PHY - Physical media attachment (PMA) requirements | 14 |
| 6.8.4 PHY - Physical media dependent (PMD) sub-layer requirements | 15 |
| Annex A (informative) Compatibility between test equipment and in-vehicle network connected to diagnostic link connector | 17 |
| Bibliography | 18 |