

ISO 11898-2:2024-03 (E)

Road vehicles - Controller area network (CAN) - Part 2: High-speed physical medium attachment (PMA) sublayer

Contents		Page
Foreword		iv
Introduction		v
1 Scope		1
2 Normative references		1
3 Terms and definitions		1
4 Abbreviated terms		3
5 HS-PMA function		4
5.1	Base requirements	4
5.2	HS-PMA test circuit	5
5.3	Static parameter	5
5.3.1	Maximum ratings of V_{CAN_H} , V_{CAN_L} and V_{Diff}	5
5.3.2	Recessive output characteristics, bus biasing active	6
5.3.3	Recessive output characteristics, bus biasing inactive	6
5.3.4	Dominant output characteristics	7
5.3.5	Maximum driver output current	8
5.3.6	PMA static receiver input characteristics, bus biasing active and inactive	9
5.3.7	Receiver input resistance	9
5.3.8	Maximum leakage currents of CAN_H and CAN_L	10
5.4	Dynamic parameter	11
5.4.1	Driver symmetry	11
5.4.2	Optional transmit dominant timeout	11
5.4.3	Transmitter and receiver timing behaviour	11
5.5	Wake-up from low-power mode	15
5.5.1	Wake-up procedures	15
5.5.2	General requirement	15
5.5.3	Basic wake-up	15
5.5.4	Via wake-up pattern	15
5.5.5	Selective wake-up	18
5.5.6	Bus biasing procedure	23
6 Conformance		25
Annex A (normative) HS-PMA with SIC mode and FAST mode		26
Annex B (informative) ECU and network design		55
Annex C (informative) PN physical layer modes		63
Bibliography		64