

DIN/TS 70121:2024-11 (E)

Electromobility - Digital communication between a d.c. EV charging station and an electric vehicle for control of d.c. charging in the Combined Charging System; Text in English

Inhalt	Seite
Foreword	11
Introduction.....	12
1 Scope.....	13
2 Normative references	13
3 Terms and definitions.....	15
4 Symbols and abbreviations	20
5 Relation to other standards	22
6 Conventions.....	22
6.1 Definition of OSI based services	22
6.2 Requirement structure.....	22
6.2.1 Requirement format.....	22
6.2.2 Applicability	23
6.2.3 Usage of RFC references	23
6.3 Notation used for XML schema diagrams	23
7 DC charging system architecture.....	24
7.1 System schematics of DC charging system	24
7.2 Pilot function	24
7.3 Communication stack.....	24
8 EV-EVSE communication	25
8.1 Basic requirements for V2G communication	25
8.1.1 General information and definitions	25
8.2 Service primitive concept of OSI layered architecture.....	25
8.2.1 Overview	25
8.2.2 Syntax of service primitives.....	26
8.3 Physical and Data Link Layer	26
8.3.1 System architecture.....	26
8.3.2 Connection coordination	29
8.3.3 EV - EVSE matching process.....	29
8.3.4 Timings, parameters and error handling	48
8.3.5 Error handling.....	52
8.3.6 EMC requirements.....	64
8.3.7 Coupling circuit.....	65
8.3.8 Layer 2 interfaces.....	74
8.3.9 Sleep and Wake-up Handling.....	75
8.4 V2G communication states.....	76
8.4.1 V2G communication of the EVCC	76
8.4.2 V2G communication of the SECC.....	78
8.5 Network layer.....	81
8.5.1 General.....	81
8.5.2 Applicable RFCs and limitations and protocol parameter settings.....	81
8.5.3 IP addressing	82
8.5.4 Network Layer service primitive — N-IP_Address.indication.....	83

8.5.5	SECC discovery	83
8.6	Transport Layer.....	84
8.6.1	Transmission control protocol (TCP).....	84
8.6.2	User datagram protocol (UDP)	85
8.7	V2G transfer protocol	85
8.7.1	General information.....	85
8.7.2	Supported ports.....	85
8.7.3	Protocol data unit.....	86
8.8	Presentation layer	89
8.8.1	XML and efficient XML interchange (EXI).....	89
8.9	Application layer	92
8.9.1	Vehicle to grid application layer messages.....	92
8.9.2	Application layer service primitives.....	92
8.9.3	SECC Discovery protocol	95
9	Application layer messages	101
9.1	General information and definitions.....	101
9.2	Protocol handshake.....	101
9.2.1	Handshake request-response message pair.....	101
9.2.2	Message definition supportedAppProtocolReq and supportedAppProtocolRes	102
9.3	Message structure	106
9.3.1	Overview	106
9.3.2	Message definition.....	106
9.3.3	Message header definition	108
9.3.4	Message body definition	109
9.4	BodyElement Definitions.....	109
9.4.1	Common Messages.....	109
9.4.2	DC messages.....	124
9.5	Complex data types.....	133
9.5.1	Overview	133
9.5.2	Common types.....	133
9.5.3	DC specific types.....	143
9.5.4	Use of optional schema elements.....	152
9.6	Session timing and error handling	157
9.6.1	Overview	157
9.6.2	Message sequence and performance timing definitions	158
9.6.3	EVCC timing and error handling for request-response message pairs.....	162
9.6.4	SECC timing and error handling for response-request message sequence	162
9.6.5	V2G communication session timing definitions.....	163
9.7	Message sequences	169
9.7.1	Protocol flow stages and associated messages.....	169
9.7.2	Basic definitions for error handling.....	170
9.7.3	Response code usage by the SECC	170
9.7.4	Request-response message sequence requirements.....	172
9.7.5	Message sequence example of successful DC charging session.....	186
Annex A (normative)	XML Schema application layer messages	189
A.1	Overview	189
A.2	V2G_CI_AppProtocol.xsd	189
A.3	V2G_CI_MsgDef.xsd.....	190
A.4	V2G_CI_MsgHeader.xsd.....	191
A.5	V2G_CI_MsgBody.xsd	191
A.6	V2G_CI_MsgDataTypes.xsd	201
A.7	xmldsig-core-schema.xsd	214
Annex B (informative)	Difference between multi-network broadcast, broadcast and unicast	220
Annex C (informative)	SLAC attenuation calculation example	221
Annex D (informative)	Begriffe	223

Annex E (informative) Modified requirements.....	229
Bibliography.....	231

Figures

Figure 1 — Communication relationship between EV, EVSE, and BS.....	13
Figure 2 — Protocol stack for DC charging control without security.....	25
Figure 3 — OSI layered architecture principles.....	25
Figure 4 — EVSE discovery process from EV side.....	32
Figure 5 — Matching state machine.....	33
Figure 6 — Sequence chart of HomePlug Green PHY matching process.....	34
Figure 7 — Example of toggle sequence with 2 toggles.....	41
Figure 8 — Matching timing sequence chart.....	50
Figure 9 — CM_SLAC_PARM.REQ/CNF sequence chart.....	53
Figure 10 — Signal strength measurement Sequence Chart.....	55
Figure 11 — Matching validation sequence chart.....	58
Figure 12 — Logical network parameter exchange sequence chart.....	60
Figure 13 — Joining the logical network sequence chart.....	62
Figure 14 — Amplitude map exchange sequence chart.....	63
Figure 15 — Implementation of parallel injection.....	65
Figure 16 — HomePlug Green PHY-transmission path example with SLAC relevant attenuations and calculations.....	68
Figure 17 — Measurement setup.....	70
Figure 18 — Implementation example with a HomePlug Green PHY coupling transformer.....	72
Figure 19 — Overview sources of crosstalk.....	73
Figure 20 — Example of valid crosstalk filter in the case of HPGP signals.....	74
Figure 21 — OSI Layer 1-2 overview.....	74
Figure 22 — Overview V2G communication states EVCC.....	78
Figure 23 — Overview V2G communication states SECC.....	80
Figure 24 — V2GTP message structure.....	86
Figure 25 — V2GTP message header structure.....	87

Figure 26 — V2GTP generic header handler.....	89
Figure 27 — Basic concept of EXI.....	91
Figure 28 — SECC discovery request message payload.....	97
Figure 29 — SECC discovery response message payload.....	99
Figure 30 — Schema Diagram — supportedAppProtocolReq.....	103
Figure 31 — Schema Diagram — supportedAppProtocolRes.....	103
Figure 32 — Schema diagram — V2G message	107
Figure 33 — Schema diagram — message header	108
Figure 34 — Schema diagram — message body.....	109
Figure 35 — Schema diagram — SessionSetupReq.....	110
Figure 36 — Schema diagram — SessionSetupRes	111
Figure 37 — Schema diagram — ServiceDiscoveryReq.....	112
Figure 38 — Schema diagram — ServiceDiscoveryRes	114
Figure 39 — Schema diagram — ServicePaymentSelectionReq.....	115
Figure 40 — Schema diagram — ServicePaymentSelectionRes	115
Figure 41 — Schema diagram — ContractAuthenticationReq	116
Figure 42 — Schema diagram — ContractAuthenticationRes.....	117
Figure 43 — Schema diagram — ChargeParameterDiscoveryReq	118
Figure 44 — Schema diagram — ChargeParameterDiscoveryRes.....	119
Figure 45 — Schema diagram — PowerDeliveryReq.....	121
Figure 46 — Schema diagram — PowerDeliveryRes.....	122
Figure 47 — Schema diagram — SessionStopReq	123
Figure 48 — Schema diagram — SessionStopRes.....	123
Figure 49 — Schema diagram — CableCheckReq.....	124
Figure 50 — Schema diagram — CableCheckRes	125
Figure 51 — Schema diagram — PreChargeReq.....	126
Figure 52 — Schema diagram — PreChargeRes	126
Figure 53 — Schema diagram — CurrentDemandReq.....	128
Figure 54 — Schema diagram — CurrentDemandRes	130

Figure 55 — Schema diagram — WeldingDetectionReq	132
Figure 56 — Schema diagram — WeldingDetectionRes.....	133
Figure 57 — Schema diagram — ServiceTagType.....	133
Figure 58 — Schema diagram — ServiceType	134
Figure 59 — Schema diagram — ServiceChargeType	135
Figure 60 — Schema diagram — PhysicalValueType.....	136
Figure 61 — Schema diagram — PaymentOptionsType.....	137
Figure 62 — Schema diagram — XML Schema Definition for the ChargingProfileType	138
Figure 63 — Schema diagram — ProfileEntryType	138
Figure 64 — Schema diagram — SAScheduleListType.....	139
Figure 65 — Schema diagram — SAScheduleTupleType	140
Figure 66 — Schema diagram — PMaxScheduleType.....	141
Figure 67 — Schema diagram — PMaxScheduleEntryType	141
Figure 68 — Schema diagram — RelativeTimeIntervalType	142
Figure 69 — Schema diagram — SelectedServiceListType	143
Figure 70 — Schema Diagram — SelectedServiceType	143
Figure 71 — Schema diagram — DC_EVSEStatusType	144
Figure 72 — Schema diagram — DC_EVStatusType	146
Figure 73 — Schema diagram — DC_EVChargeParameterType	148
Figure 74 — Schema diagram — DC_EVSEChargeParameterType.....	150
Figure 75 — Schema diagram — DC_EVPowerDeliveryParameterType.....	151
Figure 76 — Message sequence and performance timing	161
Figure 77 — V2G communication session timing.....	168
Figure 78 — Initialization sequence between EV and EVSE.....	186
Figure 79 — Initialization sequence (cont.) between EV and EVSE.....	187
Figure 80 — Pre-charge and energy transfer sequence between EV and EVSE	188
Figure 81 — Welding Detection and terminate charging sequence between EV and EVSE	188
Figure A.1 — Dependency chart of the V2G CI XML schema definitions	189
Figure C.1 — SLAC attenuation calculation example	222

Tables

Table 1 — ROBO modes and PHY data rate 28

Table 2 — SLAC MME parameter values 35

Table 3 — EV_Discovering_Status definition 40

Table 4 — MME parameters for Validation, first request-response 43

Table 5 — MME parameters for validation, second request-response 44

Table 6 — CM_AMP_MAP.REQ parameters 47

Table 7 — CM_AMP_MAP.CNF parameters 47

Table 8 — Timings and parameters 51

Table 9 — Notched carriers 64

Table 10 — Signal requirements for parallel HomePlug Green PHY injection to Control Pilot 66

Table 11 — Component values of HomePlug Green PHY coupling Implementation example 72

Table 12 — Mandatory ICMP message set 82

Table 13 — N-IP_Address.indication service primitive 83

Table 14 — Supported ports for V2GTP 85

Table 15 — Generic V2GTP header structure 87

Table 16 — Overview on V2GTP payload types 88

Table 17 — Excluded EXI coding options 91

Table 18 — EXI profile settings 91

Table 19 — A-Data.confirmation service primitive 92

Table 20 — A-Data.response service primitive 93

Table 21 — A-Data.request service primitive 94

Table 22 — A-Data.indication service primitive 95

Table 23 — Payload type SECC discover request message 98

Table 24 — N-SECC_Address.indication service primitive 100

Table 25 — Semantics and type definition for supportedAppProtocol message elements 103

Table 26 — Semantics and type definition for a V2G message 107

Table 27 — Semantics and type definition for a V2G message header 109

Table 28 — Semantics and type definition for a V2G message body 109

Table 29 — Semantics and type definition for SessionSetupReq	111
Table 30 — Semantics and type definition for SessionSetupRes.....	111
Table 31 — Semantics and type definition for ServiceDiscoveryReq	113
Table 32 — Semantics and type definition for ServiceDiscoveryRes.....	114
Table 33 — Semantics and type definition for ServicePaymentSelectionReq	115
Table 34 — Semantics and type definition for ServicePaymentSelectionRes	115
Table 35 — Semantics and type definition for ContractAuthenticationReq.....	116
Table 36 — Semantics and type definition for ContractAuthenticationRes	117
Table 37 — Semantics and type definition for ChargeParameterDiscoveryReq.....	118
Table 38 — Semantics for EVRequestedEnergyTransferType	118
Table 39 — Semantics and type definition for ChargeParameterDiscoveryRes	120
Table 40 — Semantics and type definition for PowerDeliveryReq.....	121
Table 41 — Semantics and type definition for PowerDeliveryRes	122
Table 42 — Semantics and type definition for SessionStopRes	123
Table 43 — Semantics and type definition for CableCheckReq	124
Table 44 — Semantics and type definition for CableCheckRes	125
Table 45 — Semantics and type definition for PreChargeReq	126
Table 46 — Semantics and type definition for PreChargeRes.....	127
Table 47 — Semantics and type definition for CurrentDemandReq	129
Table 48 — Semantics and type definition for CurrentDemandRes.....	131
Table 49 — Semantics and type definition for WeldingDetectionReq.....	132
Table 50 — Semantics and type definition for WeldingDetectionRes	133
Table 51 — Semantics and type definition for ServiceTagType	134
Table 52 — Semantics and type definition for ServiceType	135
Table 53 — Semantics and type definition for ServiceChargeType.....	135
Table 54 — Semantics for EVSESupportedEnergyTransferType.....	136
Table 55 — Semantics and type definition for PhysicalValueType	137
Table 56 — Semantics and type definition for PaymentOptionsType	137
Table 57 — Semantics and type definition for ChargingProfileType.....	138

Table 58 — Semantics and type definition for ProfileEntryType	139
Table 59 — Semantics and type definition for SAScheduleListType.....	139
Table 60 — Semantics and type definition for SAScheduleTupleType.....	140
Table 61 — Semantics and type definition for PMaxScheduleType	141
Table 62 — Semantics and type definition for PMaxScheduleEntryType	142
Table 63 — Semantics and type definition for RelativeTimeIntervalType.....	142
Table 64 — Semantics and type definition for SelectedServiceListType.....	143
Table 65 — Semantics and type definition for SelectedServiceType.....	143
Table 66 — Semantics and type definition for DC_EVSEStatusType.....	144
Table 67 — Semantics & Types of Elements in the isolationLevelType.....	145
Table 68 — Semantics and type definition for DC_EVSEStatusCodeType.....	145
Table 69 — Semantics and type definition for DC_EVStatusType	146
Table 70 — Semantics and type definition for EVErrorCodeType.....	147
Table 71 — Semantics and type definition for DC_EVChargeParameterType.....	149
Table 72 — Semantics and type definition for DC_EVSEChargeParameterType.....	151
Table 73 — Semantics and type definition for DC_EVPowerDeliveryParameterType	152
Table 74 — Optional schema elements.....	152
Table 75 — EVCC and SECC timers, timeouts, performance times.....	158
Table 76 — EVCC and SECC message timeouts and performance times.....	160
Table 77 — EVCC and SECC V2G communication session timing parameters.....	166
Table 78 — EVCC and SECC V2G communication session timing parameter values	167
Table 79 — Overview on the use of ResponseCodes	171
Table E.1 — Modified requirements.....	229