

ISO 15765-2:2024-04 (E)

Road vehicles - Diagnostic communication over Controller Area Network (DoCAN) - Part 2: Transport protocol and network layer services

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Symbols and abbreviated terms | 2 |
| 4.1 | Symbols | 2 |
| 4.2 | Abbreviated terms | 3 |
| 5 | Conventions | 4 |
| 6 | ISO 11898-1 CAN data link layer extension | 5 |
| 6.1 | CAN CC and CAN FD frame feature comparison | 5 |
| 6.2 | Mapping of transport and network layer attributes to CAN data frames | 5 |
| 7 | T_Data abstract service primitive interface definition | 7 |
| 7.1 | T_Data services | 7 |
| 7.2 | T_Data interface | 7 |
| 7.3 | Data type definitions | 8 |
| 8 | Transport and network layer services | 8 |
| 8.1 | General | 8 |
| 8.2 | Transport and network layer abstract service primitives | 9 |
| 8.2.1 | Data.req | 9 |
| 8.2.2 | Data.con | 10 |
| 8.2.3 | Data_FF.ind | 10 |
| 8.2.4 | Data.ind | 10 |
| 8.2.5 | ChangeParameter.req | 11 |
| 8.2.6 | ChangeParameter.con | 11 |
| 8.3 | Service data unit specification | 12 |
| 8.3.1 | Mtype, message type | 12 |
| 8.3.2 | AI, address information | 12 |
| 8.3.3 | <Length> | 14 |
| 8.3.4 | <MessageData> | 14 |
| 8.3.5 | <Parameter> | 14 |
| 8.3.6 | <Parameter_Value> | 14 |
| 8.3.7 | <Result> | 15 |
| 8.3.8 | <Result_ChangeParameter> | 16 |
| 8.4 | ASP T_Data to TL_Data interface parameter mapping | 16 |
| 9 | Transport layer protocol | 17 |
| 9.1 | Protocol functions | 17 |
| 9.2 | Single frame message transmission | 17 |
| 9.3 | Multiple frame message transmission | 17 |
| 9.4 | Transport layer protocol data units | 19 |
| 9.4.1 | Protocol data unit types | 19 |
| 9.4.2 | SF TL_PDU | 19 |
| 9.4.3 | FF TL_PDU | 19 |
| 9.4.4 | CF TL_PDU | 19 |
| 9.4.5 | FC TL_PDU | 19 |
| 9.4.6 | TL_PDU field specification | 19 |

| | | |
|-----------|--|-----------|
| 9.5 | Transmit data length (TX_DL) configuration..... | 20 |
| 9.5.1 | Definition of TX_DL configuration values..... | 20 |
| 9.5.2 | Verifying the correctness of received CAN frames..... | 20 |
| 9.5.3 | Receiver determination RX_DL..... | 21 |
| 9.6 | Protocol control information specification..... | 22 |
| 9.6.1 | TL_PCI..... | 22 |
| 9.6.2 | SingleFrame TL_PCI parameter definition..... | 23 |
| 9.6.3 | FirstFrame TL_PCI parameter definition..... | 25 |
| 9.6.4 | ConsecutiveFrame TL_PCI parameter definition..... | 26 |
| 9.6.5 | FlowControl TL_PCI parameter definition..... | 27 |
| 9.7 | Maximum number of FC.WAIT frame transmissions (C_{TL_WFTmax})..... | 31 |
| 9.8 | Transport layer timing..... | 31 |
| 9.8.1 | Timing parameters..... | 31 |
| 9.8.2 | Transport layer timeouts..... | 35 |
| 9.8.3 | Unexpected arrival of TL_PDU..... | 35 |
| 9.8.4 | Wait frame error handling..... | 36 |
| 9.9 | Interleaving of messages..... | 37 |
| 10 | Network layer protocol..... | 37 |
| 10.1 | Protocol data unit field specification..... | 37 |
| 10.1.1 | NL_PDU format..... | 37 |
| 10.1.2 | Address information (NL_AI)..... | 37 |
| 10.2 | Creating CAN frames based on NL_TAtype and TX_DL..... | 37 |
| 10.3 | Mapping of the NL_PDU fields..... | 37 |
| 10.3.1 | Addressing formats..... | 37 |
| 10.3.2 | Normal addressing..... | 37 |
| 10.3.3 | Normal fixed addressing..... | 38 |
| 10.3.4 | Extended addressing..... | 39 |
| 10.3.5 | Mixed addressing..... | 39 |
| 11 | Data link layer usage..... | 40 |
| 11.1 | Data link layer service parameters..... | 40 |
| 11.2 | Data link layer interface services..... | 41 |
| 11.3 | CAN frame data length code (DLC)..... | 41 |
| 11.3.1 | DLC parameter..... | 41 |
| 11.3.2 | CAN frame data..... | 41 |
| 11.3.3 | Data length code (DLC) error handling..... | 42 |
| | Annex A (normative) Use of normal fixed and mixed addressing according to SAE J1939-21..... | 43 |
| | Annex B (normative) Reserved CAN IDs..... | 46 |
| | Bibliography..... | 47 |