ISO 15765-2:2024-04 (E)

Road vehicles - Diagnostic communication over Controller Area Network (DoCAN) - Part 2: Transport protocol and network layer services

Contents

Page

Foreword ..... **v**

Introduction ..... **vi**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Symbols and abbreviated terms **2**
4.1 Symbols 2
4.2 Abbreviated terms 3

5 Conventions **4**

6 ISO 11898-1 CAN data link layer extension **5**
6.1 CAN CC and CAN FD frame feature comparison 5
6.2 Mapping of transport and network layer attributes to CAN data frames 5

7 T_Data abstract service primitive interface definition **7**
7.1 T_Data services 7
7.2 T_Data interface 7
7.3 Data type definitions 8

8 Transport and network layer services **8**
8.1 General 8
8.2 Transport and network layer abstract service primitives 9
8.2.1 Data.req 9
8.2.2 Data.con 10
8.2.3 Data_FF.ind 10
8.2.4 Data.ind 10
8.2.5 ChangeParameter.req 11
8.2.6 ChangeParameter.con 11
8.3 Service data unit specification 12
8.3.1 Mtype, message type 12
8.3.2 AI, address information 12
8.3.3 <Length> 14
8.3.4 <MessageData> 14
8.3.5 <Parameter> 14
8.3.6 <Parameter_Value> 14
8.3.7 <Result> 15
8.3.8 <Result_ChangeParameter> 16
8.4 ASP T_Data to TL_Data interface parameter mapping 16

9 Transport layer protocol **17**
9.1 Protocol functions 17
9.2 Single frame message transmission 17
9.3 Multiple frame message transmission 17
9.4 Transport layer protocol data units 19
9.4.1 Protocol data unit types 19
9.4.2 SF TL_PDU 19
9.4.3 FF TL_PDU 19
9.4.4 CF TL_PDU 19
9.4.5 FC TL_PDU 19
9.4.6 TL_PDU field specification 19

9.5 Transmit data length (TX_DL) configuration 20
9.5.1 Definition of TX_DL configuration values 20
9.5.2 Verifying the correctness of received CAN frames 20
9.5.3 Receiver determination RX_DL 21
9.6 Protocol control information specification 22
9.6.1 TL_PCI 22
9.6.2 SingleFrame TL_PCI parameter definition 23
9.6.3 FirstFrame TL_PCI parameter definition 25
9.6.4 ConsecutiveFrame TL_PCI parameter definition 26
9.6.5 FlowControl TL_PCI parameter definition 27
9.7 Maximum number of FC.WAIT frame transmissions (C_{TL_WFTmax}) 31
9.8 Transport layer timing 31
9.8.1 Timing parameters 31
9.8.2 Transport layer timeouts 35
9.8.3 Unexpected arrival of TL_PDU 35
9.8.4 Wait frame error handling 36
9.9 Interleaving of messages 37
10 Network layer protocol 37
10.1 Protocol data unit field specification 37
10.1.1 NL_PDU format 37
10.1.2 Address information (NL_AI) 37
10.2 Creating CAN frames based on NL_TAtype and TX_DL 37
10.3 Mapping of the NL_PDU fields 37
10.3.1 Addressing formats 37
10.3.2 Normal addressing 37
10.3.3 Normal fixed addressing 38
10.3.4 Extended addressing 39
10.3.5 Mixed addressing 39
11 Data link layer usage 40
11.1 Data link layer service parameters 40
11.2 Data link layer interface services 41
11.3 CAN frame data length code (DLC) 41
11.3.1 DLC parameter 41
11.3.2 CAN frame data 41
11.3.3 Data length code (DLC) error handling 42
Annex A (normative) **Use of normal fixed and mixed addressing according to SAE J1939-21 ..... 43**
Annex B (normative) **Reserved CAN IDs 46**
Bibliography 47