ISO 6621-4:2024-05 (E)

Internal combustion engines - Piston rings - Part 4: General specifications

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Piston ring codes 1

5 Designation of piston rings 4
5.1 Designation elements and order 4
5.1.1 General 4
5.1.2 Mandatory elements 4
5.1.3 Measurement principles 5
5.1.4 Additional elements 5
5.1.5 Elements for additional marking 5
5.2 Designation examples 5
5.2.1 Designation example of a piston ring in accordance with ISO 6622-1 5
5.2.2 Designation example of a piston ring in accordance with ISO 6624-1 5
5.2.3 Designation example of a piston ring in accordance with ISO 6626-1 6

6 Designation of piston rings 6
6.1 General 6
6.2 Mandatory topside identification marking 6
6.3 Additional marking 7

7 General characteristics 7
7.1 Ring shape 7
7.2 Light tightness 8
7.3 Closed gap 8
7.4 Tangential force, Ft, and diametral force, Fd, of single piece piston rings 8
7.4.1 Calculation of Ft, and Fd values in dimension tables of dimensional standards 8
7.4.2 Correction of Ft, and Fd values 9
7.4.3 Examples for correction of Ft and Fd 10
7.5 Tangential force Ft of multipiece oil control rings as specified in ISO 6626-1, ISO 6626- 2, and ISO 6626-3 12
7.5.1 General 12
7.5.2 Rounding of values 12
7.5.3 Examples for calculating tangential force Ft 12
7.6 Tangential force Ft of expander/rail oil control rings as specified in ISO 6627 13
7.6.1 General 13
7.6.2 Example for calculating the tangential force Ft -- Selected type of piston ring: ISO 6627 -ES3 - 85 × 3 - MC67 MC68/CR1 PNH 13

8 Notches for preventing ring rotation 13
8.1 Ring joint with internal notch (only for compression rings as specified in ISO 6622 and ISO 6624) 13
8.2 Ring joint with side notch (only for compression rings as specified in ISO 6622) 15

9 Machining of surfaces 16
9.1 Peripheral surfaces 16
9.2 Side faces 16
9.3 Other surfaces 16

10 Plated, coated, and treated surfaces 17
10.1 Chromium plating on peripheral and side surfaces 17
10.1.1 General 17
10.1.2 Chromium plating thickness 17
10.1.3 Chromium plated rings of fully faced design 17

10.1.4 Chromium plated rings of semi-inlaid design 17
10.1.5 Chromium plated rings of inlaid design 18
10.1.6 Side Chromium plated rings design 19
10.1.7 Radius, chamfer and dimensions of peripheral edges of chromium plated rings 19
10.1.8 Peripheral edges at the gap of chromium plated rings and rails 20
10.1.9 Hardness of chromium plating 21
10.2 Spray-coated peripheral surfaces 21
10.2.1 Codes 21
10.2.2 Spray-coating thickness 21
10.2.3 Spray-coated rings of fully faced design 21
10.2.4 Spray-coated rings of semi-inlaid design 21
10.2.5 Spray-coated rings of inlaid design 22
10.2.6 Radius, chamfer of peripheral edges of spray-coated rings 23
10.2.7 Peripheral edges at gap of spray-coated rings 23
10.2.8 Hardness of spray-coating 24
10.3 Nitride surfaces 24
10.3.1 Codes 24
10.3.2 Nitride case depth 24
10.3.3 Radius and dimensions of outside and inside edges of nitride steel rings 25
10.3.4 Peripheral edges at the gap of nitride steel rings and rails 25
10.4 Treated surfaces 26
10.4.1 Ferro-oxidized all over -- Code FE -- Coating thickness (0,001 to 0,005) mm 26
10.4.2 Phosphated all over -- Code PO -- Coating thickness 0,002 mm min 26
10.4.3 Phosphated all over -- Code PR -- Coating thickness 0,002 mm max 26
10.5 Physical vapour deposition coating (PVD) 26
10.5.1 Codes 26
10.5.2 PVD coating 26
10.5.3 PVD coating thickness 26
10.5.4 Hardness of PVD coating 26
10.5.5 Peripheral edges at the gap of PVD-coated rings and rails 27

11 Miscellaneous 27
11.1 Cleanliness 27
11.2 Corrosion protection 27
11.3 Packaging 27

12 Traceability (optional) 27

Bibliography 28