

ISO 6621-4:2024-05 (E)

Internal combustion engines - Piston rings - Part 4: General specifications

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Piston ring codes | 1 |
| 5 | Designation of piston rings | 4 |
| 5.1 | Designation elements and order | 4 |
| 5.1.1 | General | 4 |
| 5.1.2 | Mandatory elements | 4 |
| 5.1.3 | Measurement principles | 5 |
| 5.1.4 | Additional elements | 5 |
| 5.1.5 | Elements for additional marking | 5 |
| 5.2 | Designation examples | 5 |
| 5.2.1 | Designation example of a piston ring in accordance with ISO 6622-1 | 5 |
| 5.2.2 | Designation example of a piston ring in accordance with ISO 6624-1 | 5 |
| 5.2.3 | Designation example of a piston ring in accordance with ISO 6626-1 | 6 |
| 6 | Designation of piston rings | 6 |
| 6.1 | General | 6 |
| 6.2 | Mandatory topside identification marking | 6 |
| 6.3 | Additional marking | 7 |
| 7 | General characteristics | 7 |
| 7.1 | Ring shape | 7 |
| 7.2 | Light tightness | 8 |
| 7.3 | Closed gap | 8 |
| 7.4 | Tangential force, F_t , and diametral force, F_d , of single piece piston rings | 8 |
| 7.4.1 | Calculation of F_t , and F_d values in dimension tables of dimensional standards | 8 |
| 7.4.2 | Correction of F_t , and F_d values | 9 |
| 7.4.3 | Examples for correction of F_t and F_d | 10 |
| 7.5 | Tangential force F_t of multipiece oil control rings as specified in ISO 6626-1, ISO 6626-2, and ISO 6626-3 | 12 |
| 7.5.1 | General | 12 |
| 7.5.2 | Rounding of values | 12 |
| 7.5.3 | Examples for calculating tangential force F_t | 12 |
| 7.6 | Tangential force F_t of expander/rail oil control rings as specified in ISO 6627 | 13 |
| 7.6.1 | General | 13 |
| 7.6.2 | Example for calculating the tangential force F_t -- Selected type of piston ring: ISO 6627 -ES3 - 85 × 3 - MC67 MC68/CR1 PNH | 13 |
| 8 | Notches for preventing ring rotation | 13 |
| 8.1 | Ring joint with internal notch (only for compression rings as specified in ISO 6622 and ISO 6624) | 13 |
| 8.2 | Ring joint with side notch (only for compression rings as specified in ISO 6622) | 15 |

| | | |
|--------|---|----|
| 9 | Machining of surfaces | 16 |
| 9.1 | Peripheral surfaces | 16 |
| 9.2 | Side faces | 16 |
| 9.3 | Other surfaces | 16 |
| 10 | Plated, coated, and treated surfaces | 17 |
| 10.1 | Chromium plating on peripheral and side surfaces | 17 |
| 10.1.1 | General | 17 |
| 10.1.2 | Chromium plating thickness | 17 |
| 10.1.3 | Chromium plated rings of fully faced design | 17 |
| 10.1.4 | Chromium plated rings of semi-inlaid design | 17 |
| 10.1.5 | Chromium plated rings of inlaid design | 18 |
| 10.1.6 | Side Chromium plated rings design | 19 |
| 10.1.7 | Radius, chamfer and dimensions of peripheral edges of chromium plated rings | 19 |
| 10.1.8 | Peripheral edges at the gap of chromium plated rings and rails | 20 |
| 10.1.9 | Hardness of chromium plating | 21 |
| 10.2 | Spray-coated peripheral surfaces | 21 |
| 10.2.1 | Codes | 21 |
| 10.2.2 | Spray-coating thickness | 21 |
| 10.2.3 | Spray-coated rings of fully faced design | 21 |
| 10.2.4 | Spray-coated rings of semi-inlaid design | 21 |
| 10.2.5 | Spray-coated rings of inlaid design | 22 |
| 10.2.6 | Radius, chamfer of peripheral edges of spray-coated rings | 23 |
| 10.2.7 | Peripheral edges at gap of spray-coated rings | 23 |
| 10.2.8 | Hardness of spray-coating | 24 |
| 10.3 | Nitride surfaces | 24 |
| 10.3.1 | Codes | 24 |
| 10.3.2 | Nitride case depth | 24 |
| 10.3.3 | Radius and dimensions of outside and inside edges of nitride steel rings | 25 |
| 10.3.4 | Peripheral edges at the gap of nitride steel rings and rails | 25 |
| 10.4 | Treated surfaces | 26 |
| 10.4.1 | Ferro-oxidized all over -- Code FE -- Coating thickness (0,001 to 0,005) mm | 26 |
| 10.4.2 | Phosphated all over -- Code PO -- Coating thickness 0,002 mm min | 26 |
| 10.4.3 | Phosphated all over -- Code PR -- Coating thickness 0,002 mm max | 26 |
| 10.5 | Physical vapour deposition coating (PVD) | 26 |
| 10.5.1 | Codes | 26 |
| 10.5.2 | PVD coating | 26 |
| 10.5.3 | PVD coating thickness | 26 |
| 10.5.4 | Hardness of PVD coating | 26 |
| 10.5.5 | Peripheral edges at the gap of PVD-coated rings and rails | 27 |
| 11 | Miscellaneous | 27 |
| 11.1 | Cleanliness | 27 |
| 11.2 | Corrosion protection | 27 |
| 11.3 | Packaging | 27 |
| 12 | Traceability (optional) | 27 |
| | Bibliography | 28 |