

# ISO 22760-9:2024-05 (E)

## Road vehicles - Dimethyl Ether (DME) fuel system components - Part 9: Pressure relief device (PRD)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Marking .....</b>	<b>2</b>
<b>5</b>	<b>Design and assembly .....</b>	<b>2</b>
<b>6</b>	<b>Tests .....</b>	<b>2</b>
6.1	Applicability .....	2
6.2	Hydrostatic strength .....	3
6.3	Leakage .....	3
6.4	Bending moment .....	3
6.5	Continued operation .....	4
6.5.1	Test procedure .....	4
6.5.2	Requirements .....	4
6.6	Accelerated life .....	4
6.6.1	General .....	4
6.6.2	Test procedure .....	4
6.6.3	Accelerated-life test temperature .....	4
6.6.4	Requirements .....	5
6.7	Benchtop activation .....	5
6.7.1	General .....	5
6.7.2	Thermally-activated PRDs .....	5
6.8	Thermal cycling .....	5
6.8.1	Test procedure .....	5
6.8.2	Requirements .....	6
6.9	Condensate corrosion resistance .....	6
6.9.1	Test procedure .....	6
6.9.2	Test solution .....	6
6.10	Flow capacity .....	6
6.10.1	General .....	6
6.10.2	Test procedure .....	6
<b>7</b>	<b>Production batch inspection and acceptance testing .....</b>	<b>7</b>
<b>Annex A (normative)</b>	<b>Determination of fusible material yield temperature and PRD activation temperature .....</b>	<b>8</b>
<b>Bibliography .....</b>		<b>9</b>