

# ISO 24605:2024-06 (E)

## Road vehicles - Dimethyl ether (DME) refuelling connector with pressure equalizing port

---

<b>Contents</b>		<b>Page</b>
Foreword		iv
Introduction		v
<b>1</b>	<b>Scope</b>	<b>1</b>
<b>2</b>	<b>Normative references</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions</b>	<b>1</b>
<b>4</b>	<b>General construction requirements</b>	<b>3</b>
<b>5</b>	<b>Nozzles</b>	<b>3</b>
<b>6</b>	<b>Standard receptacle dimensions</b>	<b>4</b>
<b>7</b>	<b>Receptacles</b>	<b>5</b>
<b>8</b>	<b>Instructions</b>	<b>6</b>
<b>9</b>	<b>Marking</b>	<b>6</b>
<b>10</b>	<b>Tests</b>	<b>7</b>
10.1	General requirements	7
10.2	Impact resistance	7
10.2.1	Nozzle test	7
10.2.2	Receptacle test	8
10.3	Leakage at room temperature	8
10.4	Abnormal loads	9
10.4.1	Test in unpressurised condition	10
10.4.2	Test in pressurised condition	10
10.5	Mounting hardware torque	10
10.6	Leakage at low and high temperatures	10
10.7	Nozzle freezing	10
10.8	Durability	11
10.8.1	Endurance	11
10.8.2	Corrosion resistance	12
10.8.3	Brass material compatibility	12
10.8.4	Resistance to dry heat	13
10.8.5	Ozone ageing	13
10.8.6	Temperature cycle	13
10.8.7	Compatibility to dimethyl ether	13
10.8.8	Electrical continuity	14
10.9	Hydrostatic strength	14
10.10	Oxygen ageing	14
10.11	Non-metallic material immersion	14
10.12	Vibration resistance	15
10.13	Creep	16
10.14	Automotive fluid exposure	16
10.14.1	General	16
10.14.2	Test method	16
10.14.3	Fluids	17
10.14.4	Pass criteria	17
<b>Annex A</b> (normative)	<b>Critical dimensions of the nozzles</b>	<b>18</b>
<b>Annex B</b> (normative)	<b>Manufacturing and production test plan</b>	<b>19</b>
<b>Bibliography</b>		<b>20</b>