

ISO 6626-2:2024-07 (E)

Internal combustion engines - Piston rings - Part 2: Coil-spring-loaded oil control rings of narrow width made of cast iron

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Overview	1
5	Piston ring types and designation	2
5.1	Types DFS-C, DFS-CNP, SSF, GSF, DSF, DSF-NG, and SSF-L — General features and dimensions	2
5.2	Type DSF-C — Coil-spring loaded bevelled edge oil control ring, chromium plated and profile ground	2
5.2.1	General features and dimensions	2
5.2.2	Designation of a Type DSF-C piston ring in accordance with ISO 6626-2	3
5.3	Type DSF-CNP — Coil-spring loaded bevelled edge oil control ring, chromium plated not profile ground	4
5.3.1	General features and dimensions	4
5.3.2	Designation of a Type DSF-CNP piston ring in accordance with ISO 6626-2	4
5.4	Type SSF — Coil-spring loaded slotted oil control ring with rectangular groove	5
5.4.1	General features and dimensions	5
5.4.2	Designation of a Type SSF piston ring in accordance with ISO 6626-2	5
5.5	Type GSF — Coil-spring loaded double bevelled oil control ring	5
5.5.1	General features and dimensions	5
5.5.2	Designation of a Type GSF piston ring in accordance with ISO 6626-2	6
5.6	Type DSF — Coil-spring loaded bevelled edge oil control ring	6
5.6.1	General features and dimensions	6
5.6.2	Designation of a Type DSF piston ring in accordance with ISO 6626-2	7
5.7	Type DSF-NG — Coil-spring loaded bevelled edge oil control ring (face geometry similar to type DSF-C or type DSF-CNP)	7
5.7.1	General features and dimensions	7
5.7.2	Designation of a Type DSF-NG piston ring in accordance with ISO 6626-2	8
5.8	Type SSF-L — Coil-spring loaded slotted oil control ring with rectangular groove at periphery and V-shaped groove beneath	8
5.8.1	General features and dimensions	8
5.8.2	Designation of a Type SSF-L piston ring in accordance with ISO 6626-2	9
6	Common features	9
6.1	Oil drainage by slots or holes	9
6.1.1	Arrangement of slots	9
6.1.2	Slot length	11
6.1.3	Arrangement of holes	11
6.1.4	Diameter and number of holes	11
6.2	Plating thickness — DSF-C and DSF-CNP (coil-spring loaded bevelled edge oil control ring, chromium plated)	11
6.3	Peripheral edges at gap of chromium plated oil control rings	12
6.4	Spring groove, slot, and land offsets	12
7	Coil springs	12
7.1	Types of coil spring	12
7.2	Latch pin and location of small pitch in the coil spring	14
7.3	Coil spring excursion (extended gap)	14

7.4	Position of coil spring gap and fixing	15
7.5	Material.....	15
8	Tangential force and nominal contact pressure	15
8.1	Tangential force, F_t	15
8.1.1	Force factors.....	15
8.1.2	General tangential force, F_t	15
8.1.3	Actual tangential force, F_t , and tolerance.....	16
8.1.4	Normalized tangential force, F_N	16
8.2	Nominal contact pressure, p_0	16
9	Dimensions	16
	Bibliography.....	31