

ISO 6518-2:2024-08 (E)

Road vehicles - Ignition systems - Part 2: Electrical performance and function test methods

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Ignition system description | 1 |
| 5 | System load | 2 |
| 6 | Ignition parameter measurements | 2 |
| 6.1 | Available secondary (spark) voltage | 2 |
| 6.2 | Secondary output voltage (open circuit coil secondary voltage) | 3 |
| 6.3 | Minimum available voltage (loaded secondary voltage) | 3 |
| 6.4 | Secondary voltage at primary current switch on (feed forward voltage) | 4 |
| 6.5 | Zener discharge current (peak spark current) | 5 |
| 6.6 | Zener discharge duration | 6 |
| 6.7 | Zener discharge voltage | 6 |
| 6.8 | Zener discharge energy | 7 |
| 6.9 | Primary current (peak coil current) | 8 |
| 6.10 | Average current input | 9 |
| 6.11 | Primary energy | 9 |
| 6.12 | Coil secondary voltage risetime | 10 |
| 6.13 | Peak coil primary voltage | 10 |
| 6.14 | Spark timing delay (time lag/delay time) | 11 |
| 6.15 | Dwell time or dwell angle | 12 |
| 7 | Test equipment | 13 |
| 7.1 | Voltage probe (voltage divider) | 13 |
| 7.2 | Oscilloscope | 13 |
| 7.3 | Current probe | 13 |
| 7.4 | DC source | 14 |
| 7.5 | Signal generator (arbitrary waveform generator) | 14 |
| 7.6 | Secondary loading | 14 |
| 7.7 | Test bench setup | 14 |
| 8 | Test procedures for ignition system parameter measurements | 15 |
| 8.1 | General comments | 15 |
| 8.2 | Secondary voltage measurements | 16 |
| 8.3 | Secondary spark energy measurements | 17 |
| 8.4 | Miscellaneous measurements | 18 |
| 9 | Test procedures for ignition system parameter measurements | 19 |