ISO/TR 6029-1:2024-12 (E)

Intelligent transport systems - Seamless positioning for multimodal transportation in ITS stations - Part 1: General information and use case definition

Contents

Page

Foreword ..... **v**

Introduction ..... **vi**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **2**

4 Abbreviated terms **3**

5 Gap analysis of seamless positioning systems **5**
5.1 Key performance indicator (KPI) 5
5.1.1 Current KPIs 5
5.1.2 Future KPIs 5
5.2 Market applicability 5
5.3 Market benefits 5

6 Basic principles and use cases overview **6**
6.1 Basic principles 6
6.2 Use case groups and associated use cases 6

7 UC definition **7**
7.1 UCG Nomadic device (ND) — Positioning 7
7.1.1 General 7
7.1.2 UC 1.1 — Indoor positioning based on network connected environment 7
7.1.3 UC 1.2 – Indoor positioning based on network disconnected environment 7
7.1.4 UC 1.3 — Outdoor positioning based on network connected environment 7
7.1.5 UC 1.4 — Outdoor positioning based on network disconnected environment 8
7.2 UCG Mobility — Positioning initialization 8
7.2.1 General 8
7.2.2 UC 2.1 — Initial positioning when mobility is on the move outdoors 8
7.2.3 UC 2.2 — Positioning data validation in radio-shadow/distorted areas (outdoor) 8
7.2.4 UC 2.3 — Positioning data update based on RSSI (indoor) 9
7.3 UCG Mobility — Tunnel 9
7.3.1 General 9
7.3.2 UC 3.1 — Positioning in tunnel based on map data 9
7.3.3 UC 3.2 — Positioning calibration in tunnel based on the latest location 9
7.4 UCG Mobility — Entrance point (from outdoor to indoor) 10
7.4.1 General 10
7.4.2 UC 4.1 — Indoor map transmission using wireless network 10
7.4.3 UC 4.2 — Indoor map transmission using IEEE 802.11 wireless LAN 10
7.4.4 UC 4.3 — Indoor map transmission using short-range wireless network 10
7.5 UCG Mobility — Exit point (from indoor to outdoor) 11
7.5.1 General 11
7.5.2 UC 5.1 — Map-based positioning when vehicle is on the move to outdoors 11
7.5.3 UC 5.2 — The latest location-based positioning when vehicle is on the move outdoors 11
7.6 UCG Mobility — Shadow zone (indoor) 12
7.6.1 General 12
7.6.2 UC 6.1 — Positioning in indoor shadow zone (spiral structure) 12
7.6.3 UC 6.2 — Positioning in indoor shadow zone (straight vertical) 12
7.7 UCG Mobility — Distorted area of positioning data 12
7.7.1 General 12

7.7.2 UC 7.1 — Distorting network area with positioning support system (outdoor) 12
7.7.3 UC 7.2 — Distorted area without positioning support system (outdoor) 13

8 Seamless positioning concept model 13
8.1 Overview 13
8.1.1 Seamless positioning service outline 13
8.1.2 Common actors concept model 14
8.2 Definition of domains 15
8.2.1 General 15
8.2.2 Role of personal device (ND) domain and actors 16
8.2.3 Role of mobility domain and actors 19
8.2.4 Role of infrastructure domain and actors 21
8.2.5 Role of positioning domain and actors 22
8.3 Relationship between actors under domain 24
8.3.1 General 24
8.3.2 P-ITS-S domain actors 24
8.3.3 Mobility domain actors 25
8.3.4 Infrastructure domain actors 26
8.4 Domain-specific information sequence diagram 27
8.4.1 General 27
8.4.2 P-ITS-S (ND) information registration and search information sequence diagram 27
8.4.3 Mobility information sequence diagram 28
8.4.4 Infrastructure information sequence diagram 36
8.5 Data transmission by actor 37
8.5.1 General 37
8.5.2 P-ITS-S (ND) determination of PVT 37
8.5.3 PVT determination from mobility perspective 38

Bibliography 40