

ISO 15118-10:2025-03 (E)

Road vehicles - Vehicle to grid communication interface - Part 10: Physical layer and data link layer requirements for single-pair Ethernet

Contents		Page
Foreword		iv
Introduction		v
1 Scope		1
2 Normative references		1
3 Terms and definitions		1
4 Abbreviated terms		2
5 Conventions		3
5.1	Definition of OSI based services	3
5.2	Requirement structure	3
6 System architecture		3
6.1	Communication layers	3
6.1.1	Architecture	3
6.1.2	Layer 2 interfaces	4
6.1.3	Communication media	4
6.1.4	Data SAP	4
6.1.5	Service primitive concept of OSI layered architecture	6
6.2	Physical channel	6
6.2.1	General	6
6.2.2	Nodes	7
6.2.3	Requirements for the physical channel	7
6.2.4	Schematic of the coupling network	7
6.3	System requirements	8
6.3.1	Overview of basic signalling	8
6.3.2	Electric vehicle supply equipment (EVSE)	9
6.3.3	Electric vehicle (EV)	9
7 Connection coordination		10
7.1	General	10
7.2	Overview	10
7.3	Plug-in phase	10
7.3.1	General	10
7.3.2	EVSE side	10
7.3.3	EV side	10
7.4	Initialization phase	10
7.5	Loss of communication	10
7.5.1	General	10
7.5.2	EVSE side	11
7.5.3	EV side	11
7.6	Sleep mode and wake-up	11
7.6.1	General	11
7.6.2	Entering sleep mode	11
7.6.3	Wake-up	11
7.7	During a charge pause	12
8 Timing and constants		12
9 EV-EVSE communication initialization		13
9.1	Overview	13
9.2	Errors	13
10 EMC requirements		13
Bibliography		14