

ISO 17987-4:2025-06 (E)

Road vehicles - Local Interconnect Network (LIN) - Part 4: Electrical physical layer (EPL) specification 12 V/24 V

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms, definitions, symbols and abbreviated terms	1
3.1	Terms and definitions	1
3.2	Symbols	2
3.3	Abbreviated terms	5
4	Conventions	6
5	Electrical physical layer requirements	6
5.1	Bit rate deviation	6
5.1.1	General	6
5.1.2	12 V LIN systems: parameters	6
5.1.3	24 V LIN systems: parameters	7
5.2	Timing requirements	9
5.2.1	Bit timing	9
5.2.2	Synchronization procedure	9
5.2.3	Bit sample timing	10
5.3	Line driver/receiver	12
5.3.1	General configuration	12
5.3.2	Definition of supply voltages for the physical interface	12
5.3.3	Signal specification	13
5.3.4	12 V LIN systems: electrical parameters	14
5.3.5	24 V LIN systems: Electrical parameters	18
5.3.6	Line characteristics	21
5.3.7	12 V LIN systems: performance in non-operation supply voltage range	22
5.3.8	24 V LIN systems: performance in non-operation supply voltage range	22
5.3.9	Performance during fault modes	22
5.3.10	ESD/EMI compliance	22
6	Procedures C, D and E	23
Annex A (informative)	LIN peripheral interface design considerations	24
Annex B (normative)	LIN AA procedure C physical layer	29
Annex C (normative)	LIN AA procedure D physical layer	32
Annex D (normative)	LIN AA procedure E physical layer	39
Bibliography		43