ISO 7856:2025-06 (E)

Intelligent transport systems - Remote support for low speed automated driving systems (RS-LSADS) - Performance requirements, system requirements and performance test procedures

Contents

Page

Foreword ..... **v**

Introduction ..... **vi**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Symbols and abbreviated terms **3**
4.1 Symbols 3
4.2 Abbreviated terms 3

5 RS-LSADS architecture **4**

6 Functions of RS-LSADS **6**
6.1 General 6
6.2 Remote monitoring 6
6.3 Remote assistance 6
6.4 Remote driving 6

7 RS-LSADS functional scenarios **7**
7.1 Remote support scenarios 7
7.1.1 Scenario 1: Re-starting after stopping at the bus bay 7
7.1.2 Scenario 2: Entering the unsignalized intersection 8
7.1.3 Scenario 3: Entering the signalized intersection (signal information only) 9
7.1.4 Scenario 4: Entering the signalized intersection (signal information and both lateral directions check) 9
7.1.5 Scenario 5: Bypassing obstacles that block the vehicle path 10
7.1.6 Scenario 6: Out of ODD due to environmental conditions 11

8 System requirements **12**
8.1 General 12
8.2 RS-LSADS state transition diagram 12
8.2.1 State functional descriptions 14
8.2.2 State transition descriptions 15

9 Communication performance for remote support **16**
9.1 General 16
9.2 Latency in remote support 17
9.3 End-to-end information latency 17
9.4 Information update rate 18
9.5 Distance error due to latency 18
9.6 Communication messages for remote support 19
9.6.1 Vehicle data 19
9.6.2 LSADS data 20
9.6.3 Driving environment data 20
9.6.4 Driving environment audio and video information 20
9.6.5 Passenger status onboard audio and video information 20
9.6.6 Remote assistance data 20
9.6.7 Remote driving control data 20
9.6.8 Infrastructure sensors data 20
9.6.9 Infrastructure audio and video information 20

10 RS-LSADS performance requirements **21**
10.1 Remote monitoring performance 21
10.1.1 End-to-end communication requirement during remote assistance standby or remote driving standby 21
10.2 Remote assistance performance 21
10.2.1 Monitoring data for remote assistant 21
10.2.2 Roles of remote assistant 21
10.2.3 Remote assistant response to RFI 22
10.2.4 Remote assistance HMI, and video field of view and audio 23
10.2.5 End-to-end communication requirements during remote assistance 23
10.2.6 Data storage requirements for remote assistance 23
10.3 Remote driving performance 24
10.3.1 Monitoring data for remote driver 24
10.3.2 Remote driving response to RFD 24
10.3.3 Remote driving HMI, video field of view and audio 24
10.3.4 End-to-end communication requirements during remote driving 25
10.3.5 Limitations of remote driving 25
10.3.6 Alert and warning in remote driving 25
10.3.7 Data storage requirements for remote driving 25
11 Scenario evaluation test procedures **25**
11.1 General 25
11.2 Test conditions 26
11.2.1 Subject vehicle conditions 26
11.2.2 Target vehicle or objects conditions 26
11.2.3 Environmental conditions 26
11.2.4 End-to-end communication setup for scenario tests 26
11.3 Test procedures 27
11.3.1 General 27
11.3.2 Tests for remote assistance 27
11.3.3 Tests for Remote driving 38
Annex A (informative) **An Example of RS-LSADS Implementation** **46**
Annex B (informative) **An example of the interaction between the control centre and the vehicle for LSADS equipped vehicle mobility service** **47**
Annex C (informative) **Examples of remote support required scenarios and specific operations by RS-LSADS** **49**
Bibliography **57**