

# ISO 17387:2026-02 (E)

## Intelligent transport systems - Lane change decision aid systems (LCDAS) - Performance requirements and test procedures

---

### Contents

Page

|              |  |           |
|--------------|--|-----------|
| Foreword     | v  |           |
| Introduction | vi   |           |
| <b>1</b>     | <b>Scope</b> .....   | <b>1</b>  |
| <b>2</b>     | <b>Normative references</b> .....  | <b>1</b>  |
| <b>3</b>     | <b>Terms and definitions</b> .....   | <b>1</b>  |
| <b>4</b>     | <b>Classification</b> .....  | <b>4</b>  |
| 4.1          | Coverage zone classification.....  | 4         |
| 4.1.1        | General.....   | 4         |
| 4.1.2        | Type I systems.....  | 4         |
| 4.1.3        | Type II systems.....   | 5         |
| 4.1.4        | Type III systems.....  | 5         |
| 4.2          | Target vehicle closing speed classification.....                             | 5         |
| 4.3          | Optional target vehicle closing speed classification for road curvature..... | 6         |
| 4.3.1        | Overview.....  | 6         |
| 4.3.2        | Type A systems.....  | 7         |
| 4.3.3        | Type B systems.....  | 7         |
| 4.3.4        | Type C systems.....  | 8         |
| <b>5</b>     | <b>Functional requirements</b> .....   | <b>9</b>  |
| 5.1          | LCDAS state diagram.....   | 9         |
| 5.1.1        | General.....   | 9         |
| 5.1.2        | LCDAS inactive state.....  | 9         |
| 5.1.3        | Activation criteria.....   | 9         |
| 5.1.4        | LCDAS active state.....  | 10        |
| 5.2          | System performance.....  | 11        |
| 5.2.1        | General.....   | 11        |
| 5.2.2        | Minimum detectable target vehicle.....                                       | 12        |
| 5.2.3        | Requirements for the blind spot warning function.....                        | 13        |
| 5.2.4        | Requirements for the closing vehicle warning function.....                   | 14        |
| 5.2.5        | Requirements for the lane change warning function.....                       | 16        |
| 5.2.6        | System response time.....  | 17        |
| 5.3          | User interface.....  | 17        |
| 5.3.1        | LCDAS status indication.....   | 17        |
| 5.3.2        | LCDAS warning indication.....  | 17        |
| 5.3.3        | LCDAS failure indication.....  | 17        |
| 5.4          | Operation with trailers.....   | 18        |
| 5.5          | Self-test requirements.....  | 18        |
| <b>6</b>     | <b>Test requirements</b> .....   | <b>18</b> |
| 6.1          | Test target vehicle.....   | 18        |
| 6.2          | Environmental conditions.....  | 18        |
| 6.3          | Blind spot warning test requirements.....                                    | 18        |
| 6.3.1        | General.....   | 18        |
| 6.3.2        | Blind spot warning test measurement system.....                              | 18        |
| 6.3.3        | Blind spot warning test procedures.....                                      | 19        |
| 6.4          | Closing vehicle warning test requirements.....                               | 25        |
| 6.4.1        | General.....   | 25        |
| 6.4.2        | Closing vehicle warning test measurement system.....                         | 25        |
| 6.4.3        | Closing vehicle warning test procedures.....                                 | 26        |

- 6.5 Lane change warning test requirements .....31
  - 6.5.1 General .....31
  - 6.5.2 Lane change warning test measurement system.....31
  - 6.5.3 Lane change warning test procedures .....32
- Annex A (informative) Blind spot warning example cases..... 37**
- Annex B (informative) Closing vehicle warning test speeds for systems with optional curvature types..... 45**
- Bibliography.....46**