

DIN EN 17240:2026-06 (E)

Intelligent transport systems - ESafety - ECall end to end conformance testing for IMS packet switched based systems (includes Amendment :2026)

Contents		Page
European foreword		7
Introduction		8
1	Scope	9
2	Normative references	9
3	Terms and definitions	10
4	Symbols and abbreviations	15
5	Conformance	16
5.1	General	16
5.2	General conditions	16
6	General overview of the eCall transaction for pan-European eCall	17
7	How to use this Standard	21
7.1	Layout and procedures	21
7.2	System under test	21
7.3	Accelerated test procedures	22
7.4	Accelerated test procedures for IVSs	22
7.4.1	Accelerated test procedures for all types of IVS	22
7.4.2	Additional accelerated test procedures for eCall-only IVS	24
7.5	Accelerated test procedures for MNOs	25
7.6	Accelerated test procedures for PSAPs	26
8	Requirements	27
8.1	Requirements General objectives	27
8.1.1	State transitions	27
8.1.2	Classification of testing	33
8.1.3	CTP naming conventions	35
8.1.4	CTP <stage> naming convention for IVS conformance tests	35
8.2	CTP structure	36
8.3	IMS-eCall timers	37
9	Conformance test requirements for in-vehicle user equipment and systems (IVS)	38
9.1	Conformance test requirements for in-vehicle user equipment and systems for IMS-eCall	38
9.2	Test objectives and purposes	38
9.3	Taxonomy of testing	38
9.4	State transition conformance tests for in-vehicle equipment and system to comply to Standards for IMS-eCall	38
9.4.1	Use case test objectives by stage	38
9.4.2	CTP 1.1.0.1 Conformance to ETSI TS 136 523, ETSI TS 138 523 and ETSI TS 134 229 - IVS	42
9.4.3	CTP 1.1.0.2 Conformance to valid SIM/USIM - IVS	43
9.4.4	CTP 1.1.0.3 Automatic eCall triggering does not occur when engine control OFF - IVS	44
9.4.5	CTP 1.1.1.1 Power on and self-test - IVS	45
9.4.6	CTP 1.1.2.1 eCall automatically activated - IVS	46

9.4.7	CTP 1.1.2.2 Automatically triggered eCall in progress was not disconnected upon a new eCall trigger - IVS	47
9.4.8	CTP 1.1.2.3 Post-Lateral-crash performance of automatic trigger - IVS	48
9.4.9	CTP 1.1.2.4 Post-frontal-crash performance of automatic trigger - IVS	49
9.4.10	CTP 1.1.2.5 Performance of automatic trigger - Different crash types - IVS	50
9.4.11	CTP 1.1.3.1 eCall manually activated - IVS	51
9.4.12	CTP 1.1.3.2 Manually triggered eCall in progress was not disconnected upon a new eCall trigger - IVS	52
9.4.13	CTP 1.1.4.1 Test eCall activated - IVS	53
9.4.14	CTP 1.1.5.1 Network registration - IVS	54
9.4.15	CTP 1.1.5.2 Manual termination of eCall by vehicle occupants not allowed (automatically triggered eCall) - IVS	55
9.4.16	CTP 1.1.5.3.1 Manual termination of eCall by vehicle occupants not allowed (manually triggered eCall) - IVS	56
9.4.17	CTP 1.1.5.3.2 Manual "cancellation" of eCall by vehicle occupants allowed (manually triggered eCall) - IVS	57
9.4.18	CTP 1.1.5.4 Automatically triggered eCall in progress was not disconnected when engine control is switched to OFF - IVS	58
9.4.19	CTP 1.1.5.5 Manually triggered eCall in progress was not disconnected when engine control is switched to OFF - IVS	59
9.4.20	CTP 1.1.5.6 Priority over conflicting communication - IVS	60
9.4.21	CTP 1.1.6.2 SIP Invite sent - IVS	61
9.4.22	CTP 1.1.7.1 Establish session with urn:service:sos.ecall.automatic - IVS	62
9.4.23	CTP 1.1.8.1 Establish session with urn:service:sos.ecall.manual - IVS	63
9.4.24	CTP 1.1.9.1 Establish session with urn:service:test.sos.ecall - IVS	64
9.4.25	CTP 1.1.10.1 eCall is attempted when no networks are available (limited service condition) - IVS	65
9.4.26	CTP 1.1.10.2 Redial attempt completed within 2 minutes after eCall is dropped - IVS	66
9.4.27	CTP 1.1.10.5 Test eCall is not attempted in limited service condition - IVS	67
9.4.28	CTP 1.1.10.6 Remain registered after eCall is rejected and MSD acknowledged - IVS	68
9.4.29	CTP 1.1.10.7 Redial after eCall is rejected and negative AL-ACK - IVS	69
9.4.30	CTP 1.1.10.8 Redial after eCall is rejected and missing AL-ACK - IVS	70
9.4.31	CTP 1.1.10.9 Redial after eCall is not answered - IVS	71
9.4.32	CTP 1.1.10.10 Negative AL-ACK for initial MSD - IVS	73
9.4.33	CTP 1.1.10.11 Missing AL-ACK for initial MSD - IVS	74
9.4.34	CTP 1.1.10.12 IMS emergency call is attempted when no networks with set IMS eCall support indicator are available - IVS	75
9.4.35	CTP 1.1.10.13 eCall is attempted when no networks with set IMS eCall support indicator are available - IVS	76
9.4.36	CTP 1.1.10.14 IVS logs if initial MSD is not acknowledged - IVS	77
9.4.37	CTP 1.1.11.1 Send MSD with indicator set to automatic eCall activation - IVS	78
9.4.38	CTP 1.1.12.1 Send MSD to indicate manual eCall activation - IVS	79
9.4.39	CTP 1.1.13.1 Send MSD to indicate test Call activation - IVS	80
9.4.40	CTP 1.1.15.1 Voice link established - IVS	81
9.4.41	CTP 1.1.15.2 New/updated MSD received while eCall conversation in progress - IVS	82
9.4.42	CTP 1.1.15.3 New/updated MSD while eCall conversation in progress after negative AL-ACK for initial MSD - IVS	83
9.4.43	CTP 1.1.15.4 New/updated MSD while eCall conversation in progress after negative AL-ACK for initial MSD and MSD transfer via in-band modem - IVS	84
9.4.44	CTP 1.1.15.5 New/updated MSD while eCall conversation in progress after missing AL-ACK for initial MSD - IVS	86
9.4.45	CTP 1.1.15.6 New/updated MSD while eCall conversation in progress after missing AL-ACK for initial MSD and MSD transfer via in-band modem - IVS	87
9.4.46	CTP 1.1.16.2 IVS clears down the eCall upon timer T2 expiry - IVS	89
9.4.47	CTP 1.1.16.3 IVS registers recent eCalls - IVS	90
9.4.48	CTP 1.1.17.1 Call-back allowed and able to be answered by IVS - IVS	91
9.4.49	CTP 1.1.17.2 Call-back answered by IVS in the event of abnormal termination - IVS	92
9.4.50	CTP 1.1.17.3 MSD transfer occurs upon PSAP request during call-back - IVS	93
9.4.51	CTP 1.1.17.4 Remain registered for 1 hr - IVS	94
9.4.52	CTP 1.1.17.6 No redial attempt in the event of abnormal termination after MSD ACK - IVS	95
9.4.53	CTP 1.1.17.7 Capacity of backup battery - IVS	96
9.4.54	CTP 1.1.18.1 Compliance with MSD version 3 - IVS	97

9.4.55	CTP 1.1.18.2 MSD transfer using in-band modem after negative AL-ACK - IVS	98
9.4.56	CTP 1.1.18.3 MSD transfer using in-band modem after missing AL-ACK - IVS	99
9.4.57	CTP 1.1.18.4 Conformance to ETSI TS 126 269 - IVS	100
9.4.58	CTP 1.1.18.5 MSD transfer using IPv4 - IVS	101
9.4.59	CTP 1.1.18.6 MSD transfer using IPv6 - IVS	102
9.4.60	CTP 1.1.18.7 Compliance of MSD with additional data from Euro NCAP TB 040:2022 - IVS	103
9.5	State transition test descriptions for in-vehicle equipment and system to comply to Standards for IMS-eCall - additional tests for eCall-only systems	104
9.5.1	General	104
9.5.2	CTP 1.1.1.2 IVS does not perform registration after power-up - eCall-only IVS	106
9.5.3	CTP 1.1.10.4 Verify that PLMN registration procedure is executed upon initiating an eCall - eCall-only IVS	107
9.5.4	CTP 1.1.17.5 Remain registered for 1 hr 12 hr - eCall-only IVS	108
10	Conformance tests for mobile network operators	109
10.1	Test objectives and purposes	109
10.1.1	General	109
10.1.2	Default assumptions	109
10.2	Taxonomy of testing and referenced tests	109
10.3	Use case conformance tests for mobile network operator systems to comply to Standards for IMS-eCall	109
10.3.1	Conformance requirement	109
10.3.2	Use case test objectives by stage	109
10.4	State transition test descriptions for mobile network operators to demonstrate compliance with IMS-eCall standards	110
10.4.1	General	110
10.4.2	CTP 2.0.1 Keep SIMs/USIMs/eSIMs alive even though not in regular operation - MNO	112
10.4.3	CTP 2.0.2 MNO supports general eCall relevant requirements - MNO	113
10.4.4	CTP 2.0.4 Support IMS-eCall routing - MNO	115
10.4.5	CTP 2.1.2 Accept registration - Roaming - MNO	116
10.4.6	CTP 2.2.1.1 Establish automatically initiated eCall - MNO	117
10.4.7	CTP 2.2.1.2 Route call to `most appropriate' PSAP - MNO	118
10.4.8	CTP 2.2.1.3 Provide IMS emergency data/caller ID - MNO	119
10.4.9	CTP 2.2.1.4 Initial MSD transfer in an automatically initiated eCall - MNO	120
10.4.10	CTP 2.2.2.1 Establish manually initiated eCall - MNO	121
10.4.11	CTP 2.2.2.4 Initial MSD transfer in a manually initiated eCall - MNO	122
10.4.12	CTP 2.2.3.1 Establish test eCall - MNO	123
10.4.13	CTP 2.2.3.3 Provide test eCall data - MNO	124
10.4.14	CTP 2.2.3.4 Initial MSD transfer in a test eCall - MNO	125
10.4.15	CTP 2.3.1.1 MSD transfer using IPv4 - MNO	126
10.4.16	CTP 2.3.1.2 MSD transfer using IPv6 - MNO	127
10.4.17	CTP 2.3.1.3 New MSD transfer before call clear-down - MNO	128
10.4.18	CTP 2.3.1.4 New MSD transfer using in-band modem before call clear-down - MNO	129
10.4.19	CTP 2.5.1 Support call-back - MNO	130
10.4.20	CTP 2.5.2 New MSD transfer during call-back - MNO	131
10.4.21	CTP 2.5.3 Support call-back - Roaming - MNO	132
11	Conformance tests for PSAP systems	133
11.1	Test objectives and purposes	133
11.2	Taxonomy of testing	133
11.3	Use case conformance tests for PSAP systems to comply to Standards for IMS-eCall	133
11.3.1	Conformance requirement	133
11.3.2	Use case test objectives by stage	133
11.4	State transition conformance tests for PSAPs - IMS-eCall	134
11.4.1	General	134
11.4.2	CTP 3.1.0.1 Provide MNOs with appropriate routing data - Member State/ PSAP	136
11.4.3	CTP 3.1.0.2 Maintain map geo-information - PSAP	137
11.4.4	CTP 3.1.1.1 Receive automatically initiated eCall - PSAP	138
11.4.5	CTP 3.1.1.2 Receive manually initiated eCall - PSAP	139
11.4.6	CTP 3.1.1.3 Receive test eCall - PSAP	140
11.4.7	CTP 3.1.2 Interpret IMS emergency data - Caller ID and location - PSAP	141
11.4.8	CTP 3.1.7.1 Receive MSD - PSAP	142

11.4.9	CTP 3.1.7.5 Verify PSAP behaviour when MSD format check fails - PSAP	143
11.4.10	CTP 3.1.7.6 Verify PSAP behaviour when MSD contains unknown optional additional data set - PSAP	144
11.4.11	CTP 3.1.7.7 Verify PSAP behaviour when MSD contains ASN.1 extended data- elements - PSAP	145
11.4.12	CTP 3.1.7.8 Verify PSAP behaviour when MSD contains ASN.1 extended data- values - PSAP	146
11.4.13	CTP 3.1.7.9 Compliance with MSD version 2 - PSAP	147
11.4.14	CTP 3.1.7.10 Compliance with MSD version 3 - PSAP	148
11.4.15	CTP 3.1.7.11 Request MSD using in-band modem - PSAP	149
11.4.16	CTP 3.1.7.12 Receive MSD using in-band modem - PSAP	150
11.4.17	CTP 3.1.7.13 Receive MSD using IPv4 - PSAP	152
11.4.18	CTP 3.1.7.14 Receive MSD using IPv6 - PSAP	153
11.4.19	CTP 3.1.7.15 eCall is rejected and MSD acknowledged - PSAP	154
11.4.20	CTP 3.1.7.16 MSD corrupted - PSAP	155
11.4.21	CTP 3.1.7.17 Compliance of MSD with additional data from Euro NCAP TB 040:2022 - PSAP	156
11.4.22	CTP 3.1.9 Route voice and MSD to operator - PSAP	158
11.4.23	CTP 3.1.10 Display IMS-eCall data and MSD to operator - PSAP	159
11.4.24	CTP 3.1.11 Decode VIN - PSAP	160
11.4.25	CTP 3.1.12 Talk to vehicle occupants - PSAP	161
11.4.26	CTP 3.1.13 Request new MSD before call clear-down - PSAP	162
11.4.27	CTP 3.1.14.1 Call clear-down - PSAP	163
11.4.28	CTP 3.1.15 Call-back to vehicle - PSAP	164
11.4.29	CTP 3.1.16 Request new/updated MSD after call clear-down - PSAP	165
11.4.30	CTP 3.1.17 Record of not handled eCall - PSAP	166
12	Marking, labelling and packaging	167
13	Declaration of patents and intellectual property	167
Annex A (informative) MSD examples for special PSAP tests		168
A.1	General	168
A.2	Example: standard MSD (version 3)	168
A.3	Example: standard MSD (version 3) with `unknown' OAD	171
A.4	Example: MSD (version 3) with extended data-elements	174
A.5	Example: MSD (version 3) with extended data-values	180
Annex B (informative) Relation to EN 16454		185
B.1	General	185
B.2	Relation of IVS tests	185
B.3	Relation of MNO tests	186
B.4	Relation of PSAP tests	187
Bibliography		188