DIN EN 17240:2026-06 (E)

Intelligent transport systems - ESafety - ECall end to end conformance testing for IMS packet switched based systems (includes Amendment :2026)

Contents

Page

European foreword 7

Introduction 8

1 Scope 9

2 Normative references 9

3 Terms and definitions 10

4 Symbols and abbreviations 15

5 Conformance 16
5.1 General 16
5.2 General conditions 16

6 General overview of the eCall transaction for pan-European eCall 17

7 How to use this Standard 21
7.1 Layout and procedures 21
7.2 System under test 21
7.3 Accelerated test procedures 22
7.4 Accelerated test procedures for IVSs 22
7.4.1 Accelerated test procedures for all types of IVS 22
7.4.2 Additional accelerated test procedures for eCall-only IVS 24
7.5 Accelerated test procedures for MNOs 25
7.6 Accelerated test procedures for PSAPs 26

8 Requirements 27
8.1 Requirements General objectives 27
8.1.1 State transitions 27
8.1.2 Classification of testing 33
8.1.3 CTP naming conventions 35
8.1.4 CTP <stage> naming convention for IVS conformance tests 35
8.2 CTP structure 36
8.3 IMS-eCall timers 37

9 Conformance test requirements for in-vehicle user equipment and systems (IVS) 38
9.1 Conformance test requirements for in-vehicle user equipment and systems for IMS-eCall 38
9.2 Test objectives and purposes 38
9.3 Taxonomy of testing 38
9.4 State transition conformance tests for in-vehicle equipment and system to comply to Standards for IMS-eCall 38
9.4.1 Use case test objectives by stage 38
9.4.2 CTP 1.1.0.1 Conformance to ETSI TS 136 523, ETSI TS 138 523 and ETSI TS 134 229 - IVS 42
9.4.3 CTP 1.1.0.2 Conformance to valid SIM/USIM - IVS 43
9.4.4 CTP 1.1.0.3 Automatic eCall triggering does not occur when engine control OFF - IVS 44
9.4.5 CTP 1.1.1.1 Power on and self-test - IVS 45
9.4.6 CTP 1.1.2.1 eCall automatically activated - IVS 46

9.4.7 CTP 1.1.2.2 Automatically triggered eCall in progress was not disconnected upon a new eCall trigger - IVS 47
9.4.8 CTP 1.1.2.3 Post-Lateral-crash performance of automatic trigger - IVS 48
9.4.9 CTP 1.1.2.4 Post-frontal-crash performance of automatic trigger - IVS 49
9.4.10 CTP 1.1.2.5 Performance of automatic trigger - Different crash types - IVS 50
9.4.11 CTP 1.1.3.1 eCall manually activated - IVS 51
9.4.12 CTP 1.1.3.2 Manually triggered eCall in progress was not disconnected upon a new eCall trigger - IVS 52
9.4.13 CTP 1.1.4.1 Test eCall activated - IVS 53
9.4.14 CTP 1.1.5.1 Network registration - IVS 54
9.4.15 CTP 1.1.5.2 Manual termination of eCall by vehicle occupants not allowed (automatically triggered eCall) - IVS 55
9.4.16 CTP 1.1.5.3.1 Manual termination of eCall by vehicle occupants not allowed (manually triggered eCall) - IVS 56
9.4.17 CTP 1.1.5.3.2 Manual !cancellation" of eCall by vehicle occupants allowed (manually triggered eCall) - IVS 57
9.4.18 CTP 1.1.5.4 Automatically triggered eCall in progress was not disconnected when engine control is switched to OFF - IVS 58
9.4.19 CTP 1.1.5.5 Manually triggered eCall in progress was not disconnected when engine control is switched to OFF - IVS 59
9.4.20 CTP 1.1.5.6 Priority over conflicting communication - IVS 60
9.4.21 CTP 1.1.6.2 SIP Invite sent - IVS 61
9.4.22 CTP 1.1.7.1 Establish session with urn:service:sos.ecall.automatic - IVS 62
9.4.23 CTP 1.1.8.1 Establish session with urn:service:sos.ecall.manual - IVS 63
9.4.24 CTP 1.1.9.1 Establish session with urn:service:test.sos.ecall - IVS 64
9.4.25 CTP 1.1.10.1 eCall is attempted when no networks are available (limited service condition) - IVS 65
9.4.26 CTP 1.1.10.2 Redial attempt completed within 2 minutes after eCall is dropped - IVS 66
9.4.27 CTP 1.1.10.5 Test eCall is not attempted in limited service condition - IVS 67
9.4.28 CTP 1.1.10.6 Remain registered after eCall is rejected and MSD acknowledged - IVS 68
9.4.29 CTP 1.1.10.7 Redial after eCall is rejected and negative AL-ACK - IVS 69
9.4.30 CTP 1.1.10.8 Redial after eCall is rejected and missing AL-ACK - IVS 70
9.4.31 CTP 1.1.10.9 Redial after eCall is not answered - IVS 71
9.4.32 CTP 1.1.10.10 Negative AL-ACK for initial MSD - IVS 73
9.4.33 CTP 1.1.10.11 Missing AL-ACK for initial MSD - IVS 74
9.4.34 CTP 1.1.10.12 IMS emergency call is attempted when no networks with set IMS eCall support indicator are available - IVS 75
9.4.35 CTP 1.1.10.13 eCall is attempted when no networks with set IMS eCall support indicator are available - IVS 76
9.4.36 CTP 1.1.10.14 IVS logs if initial MSD is not acknowledged - IVS 77
9.4.37 CTP 1.1.11.1 Send MSD with indicator set to automatic eCall activation - IVS 78
9.4.38 CTP 1.1.12.1 Send MSD to indicate manual eCall activation - IVS 79
9.4.39 CTP 1.1.13.1 Send MSD to indicate test Call activation - IVS 80
9.4.40 CTP 1.1.15.1 Voice link established - IVS 81
9.4.41 CTP 1.1.15.2 New/updated MSD received while eCall conversation in progress - IVS 82
9.4.42 CTP 1.1.15.3 New/updated MSD while eCall conversation in progress after negative AL-ACK for initial MSD - IVS 83
9.4.43 CTP 1.1.15.4 New/updated MSD while eCall conversation in progress after negative AL-ACK for initial MSD and MSD transfer via in-band modem - IVS 84
9.4.44 CTP 1.1.15.5 New/updated MSD while eCall conversation in progress after missing AL-ACK for initial MSD - IVS 86
9.4.45 CTP 1.1.15.6 New/updated MSD while eCall conversation in progress after missing AL-ACK for initial MSD and MSD transfer via in-band modem - IVS 87
9.4.46 CTP 1.1.16.2 IVS clears down the eCall upon timer T2 expiry - IVS 89
9.4.47 CTP 1.1.16.3 IVS registers recent eCalls - IVS 90
9.4.48 CTP 1.1.17.1 Call-back allowed and able to be answered by IVS - IVS 91
9.4.49 CTP 1.1.17.2 Call-back answered by IVS in the event of abnormal termination - IVS 92
9.4.50 CTP 1.1.17.3 MSD transfer occurs upon PSAP request during call-back - IVS 93
9.4.51 CTP 1.1.17.4 Remain registered for 1 hr - IVS 94
9.4.52 CTP 1.1.17.6 No redial attempt in the event of abnormal termination after MSD ACK - IVS 95
9.4.53 CTP 1.1.17.7 Capacity of backup battery - IVS 96
9.4.54 CTP 1.1.18.1 Compliance with MSD version 3 - IVS 97

9.4.55 CTP 1.1.18.2 MSD transfer using in-band modem after negative AL-ACK - IVS 98
9.4.56 CTP 1.1.18.3 MSD transfer using in-band modem after missing AL-ACK - IVS 99
9.4.57 CTP 1.1.18.4 Conformance to ETSI TS 126 269 - IVS 100
9.4.58 CTP 1.1.18.5 MSD transfer using IPv4 - IVS 101
9.4.59 CTP 1.1.18.6 MSD transfer using IPv6 - IVS 102
9.4.60 CTP 1.1.18.7 Compliance of MSD with additional data from Euro NCAP TB 040:2022 - IVS 103
9.5 State transition test descriptions for in-vehicle equipment and system to comply to Standards for IMS-eCall - additional tests for eCall-only systems 104
9.5.1 General 104
9.5.2 CTP 1.1.1.2 IVS does not perform registration after power-up - eCall-only IVS 106
9.5.3 CTP 1.1.10.4 Verify that PLMN registration procedure is executed upon initiating an eCall - eCall-only IVS 107
9.5.4 CTP 1.1.17.5 Remain registered for 1 hr 12 hr - eCall-only IVS 108

10 Conformance tests for mobile network operators 109
10.1 Test objectives and purposes 109
10.1.1 General 109
10.1.2 Default assumptions 109
10.2 Taxonomy of testing and referenced tests 109
10.3 Use case conformance tests for mobile network operator systems to comply to Standards for IMS-eCall 109
10.3.1 Conformance requirement 109
10.3.2 Use case test objectives by stage 109
10.4 State transition test descriptions for mobile network operators to demonstrate compliance with IMS-eCall standards 110
10.4.1 General 110
10.4.2 CTP 2.0.1 Keep SIMs/USIMs/eSIMs alive even though not in regular operation - MNO 112
10.4.3 CTP 2.0.2 MNO supports general eCall relevant requirements - MNO 113
10.4.4 CTP 2.0.4 Support IMS-eCall routing - MNO 115
10.4.5 CTP 2.1.2 Accept registration - Roaming - MNO 116
10.4.6 CTP 2.2.1.1 Establish automatically initiated eCall - MNO 117
10.4.7 CTP 2.2.1.2 Route call to `most appropriate' PSAP - MNO 118
10.4.8 CTP 2.2.1.3 Provide IMS emergency data/caller ID - MNO 119
10.4.9 CTP 2.2.1.4 Initial MSD transfer in an automatically initiated eCall - MNO 120
10.4.10 CTP 2.2.2.1 Establish manually initiated eCall - MNO 121
10.4.11 CTP 2.2.2.4 Initial MSD transfer in a manually initiated eCall - MNO 122
10.4.12 CTP 2.2.3.1 Establish test eCall - MNO 123
10.4.13 CTP 2.2.3.3 Provide test eCall data - MNO 124
10.4.14 CTP 2.2.3.4 Initial MSD transfer in a test eCall - MNO 125
10.4.15 CTP 2.3.1.1 MSD transfer using IPv4 - MNO 126
10.4.16 CTP 2.3.1.2 MSD transfer using IPv6 - MNO 127
10.4.17 CTP 2.3.1.3 New MSD transfer before call clear-down - MNO 128
10.4.18 CTP 2.3.1.4 New MSD transfer using in-band modem before call clear-down - MNO 129
10.4.19 CTP 2.5.1 Support call-back - MNO 130
10.4.20 CTP 2.5.2 New MSD transfer during call-back - MNO 131
10.4.21 CTP 2.5.3 Support call-back - Roaming - MNO 132

11 Conformance tests for PSAP systems 133
11.1 Test objectives and purposes 133
11.2 Taxonomy of testing 133
11.3 Use case conformance tests for PSAP systems to comply to Standards for IMS-eCall 133
11.3.1 Conformance requirement 133
11.3.2 Use case test objectives by stage 133
11.4 State transition conformance tests for PSAPs - IMS-eCall 134
11.4.1 General 134
11.4.2 CTP 3.1.0.1 Provide MNOs with appropriate routing data - Member State/ PSAP 136
11.4.3 CTP 3.1.0.2 Maintain map geo-information - PSAP 137
11.4.4 CTP 3.1.1.1 Receive automatically initiated eCall - PSAP 138
11.4.5 CTP 3.1.1.2 Receive manually initiated eCall - PSAP 139
11.4.6 CTP 3.1.1.3 Receive test eCall - PSAP 140
11.4.7 CTP 3.1.2 Interpret IMS emergency data - Caller ID and location - PSAP 141
11.4.8 CTP 3.1.7.1 Receive MSD - PSAP 142

11.4.9 CTP 3.1.7.5 Verify PSAP behaviour when MSD format check fails - PSAP 143
11.4.10 CTP 3.1.7.6 Verify PSAP behaviour when MSD contains unknown optional additional data set - PSAP 144
11.4.11 CTP 3.1.7.7 Verify PSAP behaviour when MSD contains ASN.1 extended data- elements - PSAP 145
11.4.12 CTP 3.1.7.8 Verify PSAP behaviour when MSD contains ASN.1 extended data- values - PSAP 146
11.4.13 CTP 3.1.7.9 Compliance with MSD version 2 - PSAP 147
11.4.14 CTP 3.1.7.10 Compliance with MSD version 3 - PSAP 148
11.4.15 CTP 3.1.7.11 Request MSD using in-band modem - PSAP 149
11.4.16 CTP 3.1.7.12 Receive MSD using in-band modem - PSAP 150
11.4.17 CTP 3.1.7.13 Receive MSD using IPv4 - PSAP 152
11.4.18 CTP 3.1.7.14 Receive MSD using IPv6 - PSAP 153
11.4.19 CTP 3.1.7.15 eCall is rejected and MSD acknowledged - PSAP 154
11.4.20 CTP 3.1.7.16 MSD corrupted - PSAP 155
11.4.21 CTP 3.1.7.17 Compliance of MSD with additional data from Euro NCAP TB 040:2022 - PSAP 156
11.4.22 CTP 3.1.9 Route voice and MSD to operator - PSAP 158
11.4.23 CTP 3.1.10 Display IMS-eCall data and MSD to operator - PSAP 159
11.4.24 CTP 3.1.11 Decode VIN - PSAP 160
11.4.25 CTP 3.1.12 Talk to vehicle occupants - PSAP 161
11.4.26 CTP 3.1.13 Request new MSD before call clear-down - PSAP 162
11.4.27 CTP 3.1.14.1 Call clear-down - PSAP 163
11.4.28 CTP 3.1.15 Call-back to vehicle - PSAP 164
11.4.29 CTP 3.1.16 Request new/updated MSD after call clear-down - PSAP 165
11.4.30 CTP 3.1.17 Record of not handled eCall - PSAP 166

12 Marking, labelling and packaging 167

13 Declaration of patents and intellectual property 167

Annex A (informative) MSD examples for special PSAP tests 168

A.1 General 168
A.2 Example: standard MSD (version 3) 168
A.3 Example: standard MSD (version 3) with `unknown' OAD 171
A.4 Example: MSD (version 3) with extended data-elements 174
A.5 Example: MSD (version 3) with extended data-values 180

Annex B (informative) Relation to EN 16454 185

B.1 General 185
B.2 Relation of IVS tests 185
B.3 Relation of MNO tests 186
B.4 Relation of PSAP tests 187

Bibliography 188