ISO 23792-1:2026-03 (E)

Intelligent transport systems - Motorway chauffeur systems (MCS) - Part 1: Framework and general requirements

Contents

Page

Foreword ..... **v**

Introduction ..... **vi**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Abbreviated terms **4**

5 Characteristics of motorway chauffeur systems (MCS) **4**

5.1 General 4

5.2 Operational design domain (ODD) 5

5.2.1 General 5

5.2.2 Roadway physical characteristics 6

5.2.3 Traffic in the surrounding environment 6

5.2.4 Abnormalities in roadway operational condition 6

5.2.5 Ambient environmental conditions 6

5.3 System functionalities 7

5.3.1 General 7

5.3.2 Basic functionalities to realize in-lane operation 7

5.3.3 Lane changing functionalities 7

5.4 Classification 8

5.5 System limitations 8

5.6 Providing information to the user 8

6 General system requirements **8**

6.1 Operating conditions 8

6.1.1 General 8

6.1.2 Engagement conditions 8

6.1.3 Disengagement-triggering conditions 8

6.1.4 Direct disengagement conditions 9

6.2 State transition 9

6.2.1 General 9

6.2.2 Off state 10

6.2.3 Standby state 10

6.2.4 Nominal operation state 11

6.2.5 Requesting fallback state 12

6.3 System functions 13

6.3.1 General 13

6.3.2 Object and event detection and response (OEDR) 13

6.3.3 Vehicle motion control (VMC) 14

6.3.4 Generation of request to intervene (RTI) 14

6.3.5 Status indication 15

6.3.6 User control interface 16

6.3.7 Fallback-ready user (FRU) input detection 17

6.3.8 Motorway chauffeur system (MCS) monitoring the fallback-ready user (FRU) 18

6.3.9 Subject vehicle condition monitor 18

6.3.10 Motorway chauffeur system (MCS) condition monitor 18

6.3.11 Localization 18

6.3.12 External warning generation 18

6.3.13 Function required for route-following functionalities 18

6.3.14 Related functions 19
6.4 Requirements for continuing operation after detecting disengagement-triggering conditions 19
6.4.1 General 19
6.4.2 Classification of adverse situations 19
6.4.3 Responses to adverse situations 20
6.5 Misuse countermeasures 21
6.5.1 General 21
6.5.2 Hazardous situations involving reasonably foreseeable misuse 21
7 Minimum performance requirements of the dynamic driving task (DDT) 21
7.1 General 21
7.2 Following traffic rules 22
7.3 Operating speed range 22
7.4 Normal operation 22
7.4.1 General 22
7.4.2 Sustained longitudinal vehicle motion control 22
7.4.3 Sustained lateral vehicle motion control 23
7.4.4 Crash avoidance 23
7.5 Performance-impaired operation 24
7.6 Reaction to unresponsive fallback ready user (FRU) 24
8 Test procedures 24
8.1 General 24
8.1.1 Purpose 24
8.1.2 Driving environment 24
8.1.3 System settings and test driver roles 25
8.1.4 Common test pass criteria 25
8.1.5 Confirmation of the human machine interface (HMI) design 25
8.1.6 Success rate and number of trials 25
8.1.7 List of test scenarios 25
8.1.8 Test sites 26
8.2 Scenario 1: Reaction to unresponsive fallback-ready user 26
8.2.1 Test scenario 26
8.2.2 Pass criteria 26
8.3 Scenario 2: Direct disengagement by steering input 27
8.3.1 Test scenario 27
8.3.2 Pass criteria 27
8.4 Scenario 3: Continued operation after brake input 27
8.4.1 Test scenario 27
8.4.2 Pass criteria 27
8.5 Scenario 4: Forward vehicle braking hard 27
8.5.1 Test scenario 27
8.5.2 Pass criteria 28
8.6 Scenario 5: Aggressive cut-in from the adjacent lane 28
8.6.1 Test scenario 28
8.6.2 Pass criteria 29
8.7 Scenario 6: Obstacle in lane 29
8.7.1 Test scenario 29
8.7.2 Pass criteria 30
8.8 Scenario 8: Approaching geographical operational design domain (ODD) boundary 30
8.8.1 Test scenario 30
8.8.2 Pass criteria 30
8.9 Scenario 9: Engagement restricted outside ODD 30
8.9.1 Test scenario 30
8.9.2 Pass criteria 30
Annex A (informative) **MCS Type 2 description and design considerations 31**
Bibliography 38