

ISO 11898-2:2026-05 (E)

Road vehicles - Controller area network (CAN) - Part 2: High-speed physical medium attachment (PMA) sublayer

Contents		Page
Foreword		iv
Introduction		v
1 Scope		1
2 Normative references		1
3 Terms and definitions		1
4 Abbreviated terms		3
5 HS-PMA function		4
5.1 Base requirements		4
5.2 HS-PMA test circuit		4
5.3 Static parameter		5
5.3.1 Maximum ratings of V_{CAN_H} , V_{CAN_L} and V_{Diff}		5
5.3.2 Recessive output characteristics, bus biasing active		5
5.3.3 Recessive output characteristics, bus biasing inactive		6
5.3.4 Dominant output characteristics		6
5.3.5 Maximum driver output current		8
5.3.6 PMA static receiver input characteristics, bus biasing active and inactive		8
5.3.7 Receiver input resistance		9
5.3.8 Maximum leakage currents of CAN_H and CAN_L		10
5.4 Dynamic parameter		10
5.4.1 Driver symmetry		10
5.4.2 Optional transmit dominant timeout		11
5.4.3 Transmitter and receiver timing behaviour		11
5.5 Wake-up from low-power mode		15
5.5.1 Wake-up procedures		15
5.5.2 General requirement		15
5.5.3 Basic wake-up		15
5.5.4 Via wake-up pattern		15
5.5.5 Selective wake-up		19
5.5.6 Bus biasing procedure		24
6 Conformance		26
Annex A (normative) HS-PMA with SIC mode and FAST mode		27
Annex B (informative) ECU and network design		54
Annex C (informative) PN physical layer modes		60
Bibliography		61