

ISO 4925:2026-06 (E)

Road vehicles - Specification of non-petroleum-based brake fluids for hydraulic systems

Contents

Page

	v
	vi
Scope	1
Normative references	1
Terms and definitions	2
Materials	2
Specifications	2
Test methods	4
6.1 Viscosity	4
6.1.1 General	4
6.1.2 Repeatability (single analyst)	5
6.1.3 Reproducibility (multi-laboratory)	5
6.2 Equilibrium reflux boiling point (ERBP)	5
6.2.1 General	5
6.2.2 Preparation of apparatus	5
6.2.3 Test procedure	5
6.2.4 Repeatability (single analyst)	5
6.2.5 Reproducibility (multi-laboratory)	6
6.2.6 Wet ERBP test	6
6.3 pH	9
6.4 Fluid stability	9
6.4.1 High-temperature stability	9
6.4.2 Chemical stability	10
6.5 Corrosion	10
6.5.1 Metal strip characteristics prior to testing	10
6.5.2 Preparation of joints	10
6.5.3 Test procedure	11
6.6 Fluidity and appearance at low temperatures	11
6.6.1 At -40 °C for 144 h	11
6.6.2 At -50 °C for 6 h	11
6.7 Water tolerance	11
6.7.1 At -40 °C for 22 h	11
6.7.2 At 60 °C for 22 h	12
6.8 Compatibility and miscibility with ISO 4926 fluid	12
6.8.1 At -40 °C for 22 h	12
6.8.2 At 60 °C for 22 h	12
6.9 Resistance to oxidation	12
6.10 Effect on rubber	13
6.10.1 Test procedures	13
6.10.2 Repeatability (single analyst)	13
6.10.3 Reproducibility (multi-laboratory)	14
6.11 Reserve alkalinity in accordance with ASTM D 1121	14
6.12 Resistance to friction-induced noise	14
6.13 Resistance to friction induced wear	14

Annex A (normative) ISO 4925 styrene-butadiene rubber (SBR) brake cups for testing brake fluid	15
Annex B (normative) Corrosion test strips	18
Annex C (informative) Corrosion strip assembly	19
Annex D (normative) Standard ethylene, propylene and diene monomer (EPDM) terpolymer rubber slabstock	20
Annex E (normative) Triethylene glycol monomethyl ether (TEGME) brake fluid grade	22
Annex F (normative) Wear test in the translatory oscillation tribometer to quantify the friction-induced wear of a brake fluid in EPDM-metal contact	25
Bibliography	29