

ISO 612:1978-03 (E)

Road vehicles; Dimensions of motor vehicles and towed vehicles; Terms and definitions

| Contents | Page |
|--|------|
| 1 Scope | 1 |
| 2 Field of application | 1 |
| 3 References | 1 |
| 4 General | 1 |
| 5 Definition of the longitudinal median plane (of the vehicle) | 2 |
| 6 Terms and definitions of dimensions of motor vehicles and towed vehicles | 3 |
| 6.1 Vehicle length | 3 |
| 6.2 Vehicle width | 4 |
| 6.3 Vehicle height (unladen) | 4 |
| 6.4 Wheel space | 5 |
| 6.5 Track | 6 |
| 6.6 Front overhang | 6 |
| 6.7 Rear overhang | 6 |
| 6.8 Ground clearance | 7 |
| 6.9 Ramp angle | 7 |
| 6.10 Approach angle | 7 |
| 6.11 Departure angle | 7 |
| 6.12 Height of chassis above ground (commercial vehicles) | 8 |
| 6.13 Maximum usable length of chassis behind cab (vehicle with cab) | 8 |
| 6.14 Bodywork length | 8 |
| 6.15 Maximum internal dimensions of body (commercial vehicles) | 9 |
| 6.16 Drawgear length | 9 |
| 6.17 Drawbar length | 10 |
| 6.18 Position of towing attachment | 10 |
| 6.19 Fifth wheel lead | 11 |
| 6.20 Height of coupling face | 11 |
| 6.21 Distance between towing device and front end of towing vehicle | 12 |
| 6.22 Rear tractor clearance radius of semi-trailer | 12 |
| 6.23 Front fitting radius of semi-trailer | 12 |
| 6.24 Camber angle | 12 |
| 6.25 Kingpin inclination | 13 |
| 6.26 Kingpin offset | 13 |
| 6.27 Toe-in | 13 |
| 6.28 Castor | 14 |
| 6.29 Vertical clearance | 14 |
| 6.30 Lift | 14 |
| 6.31 Turning lacks | 14 |
| 6.32 Turning clearance circles | 15 |