

# ISO/TR 10982:1998-03 (E)

## Road vehicles - Test procedures for evaluation out-of-position vehicle occupant interactions with deploying air bags

---

<b>Contents</b>	<b>Page</b>
<b>1</b> Scope .....	<b>1</b>
<b>2</b> Normative references .....	<b>1</b>
<b>3</b> Definitions .....	<b>1</b>
<b>4</b> Test device .....	<b>2</b>
4.1 General .....	2
4.2 50th percentile male Hybrid III dummy .....	2
4.3 "Small female" Hybrid III dummy .....	2
4.4 Three-year-old child Hybrid III dummy .....	2
<b>5</b> Instrumentation .....	<b>2</b>
5.1 Adult size dummy .....	2
5.2 Three-year-old child dummy .....	3
5.3 Data requirements .....	3
5.4 Dummy test temperature .....	3
<b>6</b> Sled pulses .....	<b>3</b>
6.1 General .....	3
6.2 Mild severity crash pulse .....	3
6.3 Moderate severity crash pulse .....	3
<b>7</b> Static and dynamic tests for driver air bag systems .....	<b>6</b>
7.1 Test set-up .....	6
7.2 Prepositioned driver tests .....	6
7.3 Acceleration-induced out-of-position driver dynamic tests .....	7
<b>8</b> Static and dynamic tests for passenger air bag systems, using child dummy .....	<b>7</b>
8.1 General .....	7
8.2 Test set-up .....	7
8.3 Child dummy test positions .....	8
8.4 Child dummy static tests for passenger air bag systems .....	9
8.5 Child dummy dynamic tests for passenger air bag systems .....	9
<b>9</b> Static and dynamic tests for passenger air bag systems using adult dummies .....	<b>9</b>
9.1 General .....	9
9.2 Test set-up .....	10
9.3 Adult dummy positions near instrument panel .....	10
9.4 Adult dummy static tests for passenger air bag systems .....	10
9.5 Adult dynamic tests for passenger air bag systems .....	10
<b>Annex A (informative) Bibliography .....</b>	<b>12</b>