

# ISO/TR 10305-2:2003-02 (E)

Road vehicles — Calibration of electromagnetic field strength measuring devices —  
Part 2: IEEE standard for calibration of electromagnetic field sensors and probes, excluding antennas,  
from 9 kHz to 40 GHz

---

## Contents

CLAUSE	PAGE
1. Overview.....	9
1.1 Scope.....	9
1.2 Purpose.....	10
1.3 Background.....	10
1.4 Grades of Calibration.....	10
1.5 Generic Probe Types.....	10
2. References.....	11
3. Definitions.....	12
4. Measurement methods.....	13
4.1 Methods.....	13
4.2 Field sensor or field probe orientation during frequency domain calibration.....	14
4.3 Field probe or field sensor orientation during time domain calibration.....	15
5. Standard field generation methods.....	16
5.1 Frequency domain field generation.....	16
5.2 Time domain field generation.....	17
6. Determining uncertainty.....	17
6.1 Standard uncertainty.....	17
6.2 Combined standard uncertainty.....	17
6.3 Expanded uncertainty.....	18
6.4 Reporting uncertainty.....	18
7. Characteristics to be measured.....	18
7.1 Frequency domain calibration.....	18
7.2 Time domain calibration.....	21
8. Procedures (measurement techniques).....	22
8.1 Transfer standard sensors and probes.....	22
8.2 Transfer and working standard sensors and probes.....	22
8.3 Frequency domain calibration procedure.....	23
8.4 Time domain calibration procedure.....	26
9. Documentation.....	27
9.1 Proper documentation.....	27
9.2 Test documentation.....	27
9.3 Calibration interval.....	28
9.4 Out-of-tolerance notification.....	28
9.5 Certification to customer.....	28

ANNEX	PAGE
Annex A (normative) Grades of calibrations .....	29
A.1 Grades of calibration.....	29
A.2 Grades of calibration notation summary .....	32
A.3 Cautions and examples .....	32
Annex B (normative) methods of field generation and field calculations .....	34
B.1 Electric and magnetic field generation using a TEM cell, 9 kHz–500 MHz .....	34
B.2 Magnetic field generation using Helmholtz coils, 9 kHz to 10 MHz .....	37
B.3 Open-ended waveguide source in anechoic chamber, 200–450 MHz .....	44
B.4 Pyramidal horn antenna source in an anechoic chamber, 450 MHz–40 GHz .....	46
B.5 Waveguide chamber, 100 MHz to 2.6 GHz.....	49
B.6 Gigahertz TEM (GTEM) cell, 9 kHz to 1 GHz .....	50
B.7 Parallel plate transmission line .....	51
B.8 Conical transmission line.....	53
B.9 Cone and ground plane .....	53
Annex C (informative) Field sensor and field probe calibration factors.....	55
C.1 Cables.....	56
C.2 Other .....	57
Annex D (informative) Types of measurements .....	57
Annex E (informative) Time domain versus frequency domain measurements.....	58
Annex F (informative) Deconvolution .....	59
Annex G (informative) Burst peak measurement.....	61
Annex H (informative) Examples on determining uncertainty .....	63
H.1 Standard uncertainty .....	64
H.2 Combined standard uncertainty .....	64
H.3 Expanded uncertainty.....	64
H.4 Reporting uncertainty.....	65
Annex I (informative) Time domain pulse fidelity.....	66
Annex J (informative) Bibliography .....	68