ISO/TR 10305-2:2003-02 (E)

Road vehicles — Calibration of electromagnetic field strength measuring devices — Part 2: IEEE standard for calibration of electromagnetic field sensors and probes, excluding antennas, from 9 kHz to 40 GHz

Contents

CLAUSE PAGE

1. Overview ... 9

1.1 Scope ... 9
1.2 Purpose ... 10
1.3 Background ... 10
1.4 Grades of Calibration ... 10
1.5 Generic Probe Types ... 10

2. References ... 11

3. Definitions ... 12

4. Measurement methods ... 13

4.1 Methods ... 13
4.2 Field sensor or field probe orientation during frequency domain calibration ... 14
4.3 Field probe or field sensor orientation during time domain calibration ... 15

5. Standard field generation methods ... 16

5.1 Frequency domain field generation ... 16
5.2 Time domain field generation ... 17

6. Determining uncertainty ... 17

6.1 Standard uncertainty ... 17
6.2 Combined standard uncertainty ... 17
6.3 Expanded uncertainty ... 18
6.4 Reporting uncertainty ... 18

7. Characteristics to be measured ... 18

7.1 Frequency domain calibration ... 18
7.2 Time domain calibration ... 21

8. Procedures (measurement techniques) ... 22

8.1 Transfer standard sensors and probes ... 22
8.2 Transfer and working standard sensors and probes ... 22
8.3 Frequency domain calibration procedure ... 23
8.4 Time domain calibration procedure ... 26

9. Documentation ... 27

9.1 Proper documentation ... 27
9.2 Test documentation ... 27
9.3 Calibration interval ... 28
9.4 Out-of-tolerance notification ... 28
9.5 Certification to customer ... 28

ANNEX PAGE

Annex A (normative) Grades of calibrations 29

A.1 Grades of calibration 29
A.2 Grades of calibration notation summary 32
A.3 Cautions and examples 32

Annex B (normative) methods of field generation and field calculations 34

B.1 Electric and magnetic field generation using a TEM cell, 9 kHz–500 MHz 34
B.2 Magnetic field generation using Helmholtz coils, 9 kHz to 10 MHz 37
B.3 Open-ended waveguide source in anechoic chamber, 200–450 MHz 44
B.4 Pyramidal horn antenna source in an anechoic chamber, 450 MHz–40 GHz 46
B.5 Waveguide chamber, 100 MHz to 2.6 GHz 49
B.6 Gigahertz TEM (GTEM) cell, 9 kHz to 1 GHz 50
B.7 Parallel plate transmission line 51
B.8 Conical transmission line 53
B.9 Cone and ground plane 53

Annex C (informative) Field sensor and field probe calibration factors 55

C.1 Cables 56
C.2 Other 57

Annex D (informative) Types of measurements 57

Annex E (informative) Time domain versus frequency domain measurements 58

Annex F (informative) Deconvolution 59

Annex G (informative) Burst peak measurement 61

Annex H (informative) Examples on determining uncertainty 63

H.1 Standard uncertainty 64
H.2 Combined standard uncertainty 64
H.3 Expanded uncertainty 64
H.4 Reporting uncertainty 65

Annex I (informative) Time domain pulse fidelity 66

Annex J (informative) Bibliography 68